Man.El.Service Srl
Torino: +39 011 25 35 33 I Milano: +39 02 83 62 30 79
info@manelservice.com
Via Carlo Pittara 46 - 10151 Torino (TO) - Italy
PIVA 09031950018 - Num. REA: 1020262
SDI 5RUO82D Cap. Soc. € 20.000 I.V

WEBASTO BLUECOOL C-27 NAUTICAL CHILLER AIR CONDITIONER 27000 BTU/h

Reference: WBCL1205003D

WEBASTO BLUECOOL C-27 NAUTICAL CHILLER AIR CONDITIONER 27000 BTU/h

Webasto BlueCool C-27 is a nautical air conditioner in chilled water unit (chiller) suitable for use on boats, with a rated cooling capacity of 27000 BTU/h.

The Webasto BlueCool C-27 is a nautical air conditioner designed to provide an effective and reliable solution for indoor air conditioning in boats. Thanks to its cooling capacity, the air conditioner ensures optimal comfort in all weather conditions.

The Webasto BlueCool C-27 is a water chiller that uses a refrigeration circuit to cool water and then distributes it through a system of pipes and fans. This method of cooling offers many advantages, including quiet operation and even distribution of cool air inside the boat.

The chiller air conditioner can provide cooling to different areas of the boat, allowing the temperature in each room to be adjusted separately. This provides precise control of thermal comfort and the ability to meet the individual preferences of each passenger on board.

The Webasto BlueCool C-27 marine air conditioner is the ideal way to keep ambient air cool and clean on boats with advanced technology designed to deliver reliable performance over time. The system features low noise levels, thanks to noise-dampening technology that minimizes all vibrations during operation and a unit design that uses high-quality materials that have been pre-selected for durability.

The Touch Screen remote panel with 4.5 m cable is available as optional.

The WEBASTO BLUECOOL C-27 comes complete with:

electronics
blower

TECHNICAL CHARACTERISTICS WEBASTO BLUECOOL C-27

Cooling capacity: 27000 BTU/h / 7900 W
Heating Capacity: 27000 BTU/h / 7900 W
Power Supply Voltage: 230V
Frequency: 50 / 60 Hz
Operating current consumption: 8.6 / 9.2 A
Minimum cold water flow rate: 19 l/min
ø cold water connection: 1"
ø seawater connection: 3/4"
Minimum seawater flow rate: 21 l/min
Max. permissible ambient temperature: 45 °C

Man.El.Service Srl
Torino: +39 011 25 35 33 I Milano: +39 02 83 62 30 79
info@manelservice.com
Via Carlo Pittara 46 - 10151 Torino (TO) - Italy
PIVA 09031950018 - Num. REA: 1020262
SDI 5RUO82D Cap. Soc. € 20.000 I.V

Refrigerant: R410a
Refrigerant quantity: 750 g
Width: 440 mm
Depth: 330 mm
Height: 360 mm
Net weight: 45Kg

Looking for a product with different technical characteristics? Here you can find the area dedicated to nautical air conditioners WEBASTO or other specialized brands.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Frequency (Hz)	50
Voltage (V)	230
Refrigerating yield	27000 BTU/h / 7900W
Heating power	27000 BTU/h / 7900W
Absorbed average current, refrigerating (A)	8.6 / 9.2
Length (mm)	440
Product type	Air conditioner
Coolant	R410A
Weight (Kg)	0.4