



## HYUNDAI LS 65000 GASOLINE GENERATOR SINGLE PHASE STAGE V AVR 3.5 KW

Reference: 65000

### HYUNDAI LS 65000 GASOLINE GENERATOR SINGLE PHASE STAGE V AVR 3,5 KW

The HYUNDAI LS 65000 single/three phase generator, is equipped with a 4-stroke **StageV** engine supplied by gasoline, delivers a maximum power of 3,5KW, complete with AVR voltage regulator.

HYUNDAI LS 65000 is equipped with electric start with battery.

The HYUNDAI LS 65000 generator provides reliable power for home, work and leisure environments, safely appliances and other electronic devices. Extremely convenient sockets and controls make it easy to start and operate the generator, making these tasks extremely quick and easy.

The HYUNDAI LS 65000 generator has a convenient double-curved handle for easy mobility and storage. HYUNDAI LS 65000 has a completely steel structure and a tank with a maximum capacity of 15 lt.

#### EMISSION STANDARD STAGEV

HYUNDAI LS 65000 is equipped with "mobile" STAGEV motorization, as required by European Regulation 2016/1628. These new engines make it possible to exponentially reduce the particulate and nitrogen oxide emissions delivered by the generator into the environment, and ensure a 200% reduction in environmental impact compared to standard engines.

#### TECHNICAL CHARACTERISTICS HYUNDAI LS 65000

Phase type: Single-phase  
Continuous use power: 3 KVA / 3 KW  
Maximum power 3.5 KVA / 3.5 KW  
Engine: 4-stroke  
Engine revolutions: 3000 rpm  
Emissions standard: StageV  
Starting: Electric  
Fuel: Gasoline  
Voltage: 230 V  
Frequency: 50Hz  
Socket panel: 2 x CEE 16A 230V  
Tank capacity: 15 l  
Sound pressure: 76 dB (A) @ 7 m  
Length: 470 mm  
Width: 710 mm  
Height: 490 mm  
Dry weight: 50 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the generators or other specialized brands.

Images and technical data are not binding.

## Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	3.5
Continuous power single phase (KW)	3
Maximum power single phase (KVA)	3.5
Continuous power single phase (KVA)	3
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	2 x CEE 16A 2300V
Engine	4 Tempi
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Elettrico
Alternator	Avvolgimento in rame
Fuel tank capacity (L)	15
Acoustic pressure	76 dB(A) at 7 m
Length (mm)	470
Width (mm)	710
Height (mm)	490
Dry weight (Kg)	
Silenced	Yes
Super silenced	No
ATS Switch device	No ATS
Voltage regulator	AVR