



PRAMAC P15000 Generator 14kVA Single-Phase - Three-Phase STAGEV

Reference:

PRAMAC P15000 GENERATOR 14KVA SINGLE-PHASE - THREE-PHASE STAGE V

The PRAMAC P15000 single-phase/three-phase generator is equipped with a Stage V Honda GX690 petrol engine, capable of delivering a power output of 14 kVA.

The PRAMAC P15000 can be supplied with or without AVR.

The PRAMAC P15000 generator is a powerful device designed to provide a reliable source of energy, both in single-phase and three-phase modes, with a capacity of 14 kVA. This generator is known for its ease of installation and operation, making starting and stopping extremely simple thanks to clear and intuitive controls. In addition, it is equipped with an automatic shutdown function in case of low oil level, ensuring engine protection.

One of the distinctive strengths of this generator is the high quality of its components, which guarantees reliable and long-lasting performance. Despite its power, the generator is surprisingly lightweight and compact, making it extremely practical to use and transport under any circumstances. Its modern design adds an aesthetic touch to efficiency.

With a 40-litre tank, the PRAMAC P15000 generator has an incredible fuel consumption of only 6 litres per hour, ensuring an autonomy of around 6 continuous operating hours. This fuel efficiency makes it an economical and sustainable choice for providing power in emergency situations or in places without a stable electricity supply.

The generator is equipped with electric start, which further simplifies its use. In addition, it is fitted with a digital control unit and an advanced protection system to ensure safe operation and safeguard the genset. These features make it ideal for a wide range of applications, including construction sites, outdoor events, and emergency situations.

CONTROL SECTION

- CONTROL UNIT with 3-position key: OFF, ON local start, REM remote start
- 2-wire remote start/stop (REM)
- Connector for RSS panel (available as an accessory)
- Alarm buzzer

CONTROL PANEL

- Display: LCD with icons (52x35 mm)
- Group parameters: V - Hz - RPM - A (single-phase) - kVA - kWe - Fuel level (%)
- Parameter control and/or firmware transfer via NFC smart connection

STAGE V EMISSION STANDARD

The PRAMAC P15000 is equipped with a Stage V "mobile" engine, as required by European Regulation 2016/1628. These new engines significantly reduce particulate and nitrogen oxide emissions released into the environment by the generator, ensuring a 200% reduction in environmental impact compared to standard engines.

TECHNICAL SPECIFICATIONS PRAMAC P15000:

Phase Type: Single-phase / Three-phase
 Continuous Power: 14 kVA / 11.2 kW
 Maximum Power: 15.7 kVA / 12.6 kW
 Voltage (VAC): 230/400 V
 Frequency (Hz): 50
 Voltage Regulator: AVR (Optional)
 Starting: Electric
 Engine: Honda GX690
 Speed (RPM): 3000
 Emission Standard: Stage V
 Fuel: Gasoline
 Socket Panel: 1 x Schuko 230V 16A - 1 x CEE 230V 16A 2P - 1 x CEE 400V 16A 3P - 1 x CEE 400V 32A 3P
 Fuel Tank Capacity: 40 L
 Fuel Consumption @ 75% Load: 5.96 L/h
 Runtime @ 75% Load: 6.71 h
 Sound Pressure: 64 dB(A) @ 7 m
 Length: 1205 mm
 Width: 754 mm
 Height: 1035 mm
 Net Weight: 325 kg

Looking for a generator with different technical specifications? [CLICK HERE](#) to explore the dedicated area for PRAMAC generators or other specialized brands.

Technical Sheet

Phase	Single phase / Three phase
Maximum power three phase (KW)	12.6
Continuous power three phase (KW)	11.2
Maximum power three phase (KVA)	15.7
Continuous power three phase (KVA)	14
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x Schuko 230V 16A - 1 x CEE 230V 16A 2P - 1 x CEE 400V 16A 3P - 1 x CEE 400V 32A 3P
Engine	HONDA GX690
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Speed governor	Mechanical
Starting system	Elettrico
Engine capacity (cm ³)	688
Oil capacity (L)	1.9
Cooling	Air
Alternator	Brushless

Poles	2
Fuel tank capacity (L)	40
Consumption (L/h)	5.96 al 75% del carico
Running time (h)	6.71 al 75% del carico
Acoustic power	92 dB(A)
Acoustic pressure	64 dB(A) at 7 m
Length (mm)	1205
Width (mm)	754
Height (mm)	1035
Dry weight (Kg)	325
Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	AVR (optional)
Engine manufacturer	Honda