



HYUNDAI H3750iE GASOLINE GENERATOR SINGLE PHASE STAGE V INVERTER 3 KW

Reference: 65151

HYUNDAI H3750iE GASOLINE GENERATOR SINGLE PHASE STAGE V INVERTER 3 KW

The HYUNDAI H3750iE single phase generator, is equipped with a 4-stroke **StageV** engine supplied by gasoline, delivers a maximum power of 3KW, complete with inverter voltage regulator.

HYUNDAI H3750iE is equipped with electric start with battery.

The HYUNDAI H3750iE generator provides reliable power for home, work and leisure environments, safely appliances and other electronic devices. Extremely convenient sockets and controls make it easy to start and operate the generator, making these tasks extremely quick and easy.

The HYUNDAI H3750iE generator has a convenient double-curved handle for easy mobility and storage. HYUNDAI H3750iE has a robust structure and a tank with a maximum capacity of 12 lt.

EMISSION STANDARD STAGEV

HYUNDAI H3750iE is equipped with "mobile" STAGEV motorization, as required by European Regulation 2016/1628. These new engines make it possible to exponentially reduce the particulate and nitrogen oxide emissions delivered by the generator into the environment, and ensure a 200% reduction in environmental impact compared to standard engines.

TECHNICAL CHARACTERISTICS HYUNDAI LS 65003

Phase type: Single-phase
Continuous use power: 3 KVA / 3 KW
Maximum power 3.3 KVA / 3.3 KW
Engine: 4-stroke
Engine revolutions: 3000 rpm
Emissions standard: StageV
Starting: Electric
Fuel: Gasoline
Voltage: 230 V
Frequency: 50Hz
Socket panel: 2 x CEE 16A 230V
Tank capacity: 12 l
Sound pressure: 64 dB (A) @ 7 m
Length: 645 mm
Width: 490 mm
Height: 585 mm
Dry weight: 45 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the generators or other specialized brands.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	3.3
Continuous power single phase (KW)	3
Maximum power single phase (KVA)	3.3
Continuous power single phase (KVA)	3
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	2 x CEE 16A 230V
Engine	4 Tempi
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Elettrico
Alternator	Avvolgimento in rame
Fuel tank capacity (L)	12
Running time (h)	6
Acoustic pressure	64 dB(A) at 7 m
Length (mm)	645
Width (mm)	490
Height (mm)	585
Dry weight (Kg)	91
Silenced	Yes
Super silenced	Yes
ATS Switch device	No ATS
Voltage regulator	Inverter