



## VITRIFRIGO C90iX OCX2-FREEZER STAINLESS STEEL

Reference: 0400-0384

### VITRIFRIGO C90iX OCX2-FREEZER STAINLESS STEEL

The VITRIFRIGO C90iX OCX2 is a modern stainless steel fridge-freezer from the new OCX2 series. Its design has been completely redesigned, featuring an elegant square door in satin stainless steel and a top with a polished finish. The flexibility of positioning is maximised thanks to a single fixing profile, allowing installation either as VITRIFRIGO C90iX OCX2 door outside or VITRIFRIGO C90iX OCX2 door inside through a simple translation of the profile itself.

The fixing profile is equipped with a concealed slot that optimises perimeter ventilation, helping to maintain optimal conditions inside the refrigerator. The "Vent Position" is an innovative feature in the upper top, which allows the door to be left ajar when not in use, thus preventing the formation of mould and unpleasant odours.

The "Steelock" locking system represents a further combination of design and technology, guaranteeing a secure hold of the VITRIFRIGO C90iX OCX2 refrigerator. The possibility of Double Door Position allows the same fixing profile to be used as both VITRIFRIGO C90iX OCX2 door inside and VITRIFRIGO C90iX OCX2 door outside.

The model is equipped with an advanced cold-storage evaporator, highlighted by the termination of the model code with the letters 'AX'. This feature allows the VITRIFRIGO C90iX OCX2 refrigerator to be used even when the engine is switched off. The slot system, called 'Self venting frame', helps to improve ventilation around the VITRIFRIGO C90iX OCX2 refrigerator.

Among the technical features, the VITRIFRIGO C90iX OCX2 offers a total capacity of 90 litres, with a freezer capacity of 9.8 litres. The power supply can be 12/24Vdc, with a nominal consumption of 45 W. The door is reversible for greater versatility in installation. The overall dimensions are 533 mm in width, 560 mm in depth and 648 mm in height, with a net weight of 27 kg.

The lighting system is based on a new and efficient high-intensity LED light system. In addition, it is possible to opt for the optional VITRIFRIGO C90iX OCX2 D power unit, which offers bivalent 12/24Vdc and 100-240Vac 50/60Hz power supply.

#### TECHNICAL CHARACTERISTICS VITRIFRIGO C90iX OCX2:

Total capacity: 90  
Freezer capacity: 9.8  
Power supply: 12/24Vdc  
Nominal consumption: 45 W  
Reversible door: yes  
Total width: 533 mm  
Total depth: 560 mm  
Total height: 648 mm  
Net weight: 27 Kg

Looking for a cockpit refrigerator with different technical characteristics? [Here](#) you can find the full range VITRIFRIGO or other specialized brands.

The images and technical data are not binding and may be subject to revisions by the manufacturer.

## Technical Sheet

Input power (W)	12-24 Vdc
Length (mm)	
Width (mm)	533
Height (mm)	648
Dry weight (Kg)	27
Power consumption (W)	
Product type	
Colour	Stainless steel
Freezer (L)	9.8
Total capacity liters	90