



GENERATOR HYUNDAI 65528 THREE-PHASE SILENCED 48KW/60KVA STAGE II

Reference: 65528

Generator Hyundai 65528 Three-Phase Silenced Stagell

Generator Hyundai 65528 Three-phase Silenced Stagell Power and reliability in one.

Hyundai LG48C Three-phase Stagell is the ideal choice for those looking for a Hyundai generator, reliable and quiet generator Stagell to power your home, business or construction site.

With a power rating of 16 kW single-phase and 48 kW three-phase, this Hyundai is capable of supplying to a wide range of equipment.

Its main features include:

3900 cc Cummins engine: reliable and complies with Stagell emission regulations.

Direct injection system: provides high efficiency and low fuel consumption.

Leroy Somer alternator: robust and reliable, provides a pure sine wave ideal for powering sensitive electronic equipment.

"Waterproof" control panel: enables easy and safe monitoring and control of the generator.

Emergency safety button: ensures immediate generator shutdown in case of need.

Miniaturized and Waterproof circuit breaker: protects the generator Stagell from overloads and short circuits.

Noise level below 85 dB (at 7m): quiet operation that does not disturb the neighborhood.

IP23 degree of protection: resistant to water and dust.

Large autonomy: 120-liter tank for extended operation.

Liquid cooling system: keeps Hyundai at optimal temperatures even under severe working conditions.

Deepsea DSE6120 control unit: provides comprehensive information on the operation of the Hyundai generator Stagell.

Provision for ATS: allows automatic generator connection in case of failure.

The Hyundai 65528 Three-Phase Silenced Stagell Generator is an ideal choice for:

Private homes: provides backup power in the event of a blackout or to power high electrical equipment.

Businesses: provides business continuity during power outages.

Construction sites: provides for power tools and machinery.

With its reliability and quiet operation, Hyundai Three-Phase Silenced Stagell

is the ideal solution for all needs.

Beating heart of reliability: The mighty 3900 cc Cummins engine beats to the beat of your peace of mind,

delivering flawless performance and unprecedented durability. No more deafening noise!

State-of-the-art soundproofing technology makes this

Hyundai generator LG48C a silent companion in any setting, from home to construction site.

Flexibility without limits: A generator as versatile as you are!

Technical specifications Hyundai 65528 Three-Phase Silenced Stagell Generator:

Single/three-phase

Three-phase continuous power use: 60 KVA

Nominal power: 16/48 Kw

Max. power MF/TF: 17.7/53 Kw

Frequency: 50 Hz

Amperage: 87 A

Noise Level: 85 DB (at 7m)

IP Degree of Protection: IP23

Degree of Insulation: H/H

Altitude: < 1000m asl

Engine: Cummins

Displacement: 3900 cc

Type of Injection: Direct

No. Cylinders: 4

Engine revs: 1500/min

Emissions: Stagell

Fuel consumption 100%/75%/50% load: 13.1/9.8/6.7 Lt/h

Fuel: Diesel

Tank capacity: 120 L

Cooling System: Coolant

Control unit: DEEPSEA DSE6120

Total capacity of lubrication system: 16.4 L

Cap. total cooling system: 12 L

Alternator Model: LK224F

Exciter: Brushless, auto-exciter

Dimensions L x W x H: 2450 * 1010 * 1250 mm

Dry Weight: 1204 Kg

Predisposition: ATS model 65289

Hyundai Technology: Hyundai is at the forefront of adopting new technologies.

The company is a leader in electrification, with an ever-expanding range.

It is also constantly integrating innovations such as advanced safety systems.

If you are looking for a product similar to Hyundai Three Phase Generator click [HERE](#).

The image is purely indicative.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	17,7
Maximum power three phase (KW)	53
Continuous power three phase (KW)	48
Maximum power three phase (KVA)	66
Continuous power three phase (KVA)	60
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	Cummins 4BTA3.9-G2
Emissions Regulations	Stage 2
Engine rpm (rpm)	1500
Starting system	Elettrico
Engine capacity (cm ³)	3900
Number cylinders	4
Cooling	Liquid
Alternator	LK224F
Length (mm)	2470
Width (mm)	1010
Height (mm)	1250
Dry weight (Kg)	1204
Control unit	DeepSea DSE6120
ATS Switch device	Optional ATS
Engine manufacturer	Cummins
Continuous power amperage	87