



HYUNDAI GENERATOR THREE-PHASE SILENCED 32KW/40KVA STAGE II

Reference: 65524

HYUNDAI GENERATOR THREE-PHASE SILENCED 32KW/40KVA STAGEII

GENERATOR HYUNDAI SILENT THREE-PHASE STAGEII 32KW/40KVA Silent power at your service

The Hyundai Stagell generator represents the ultimate expression of power and reliability in a single solution.

Designed to meet the needs of individuals, businesses and construction sites,

this Hyundai generator offers a range of unbeatable benefits:

Generator High performance:

3120 displacement YTO engine: powerful, reliable and Stagell compliant

Direct injection system: efficiency and low consumption

LK184H alternator: robust and reliable, providing a pure sine wave.

Quiet operation:

Noise level below 85 dB (at 7m): ideal for residential and office environments

Safety and reliability:

Waterproof control panel: intuitive monitoring and control

Emergency button: Immediate stop in case of need

Waterproof miniature circuit breaker: overload and short-circuit protection

IP23 degree of protection: water and dust resistant

Autonomy and durability:

Large autonomy: 75-litre tank for extended operation

Liquid cooling system: Optimal temperatures even in harsh conditions

Advanced control and management:

Deepsea DSE6120 control unit

Ready for ATS: automatic connection in the event of mains failure

The Hyundai Stagell Generator is the ideal choice for:

Private homes: backup power and supply for high equipment

Companies: business continuity in the event of outages

Construction sites: for tools and machinery

The Hyundai Stagell Three-Phase Silent Generator is the ideal solution

for anyone looking for a powerful, reliable and silent Hyundai generator.

With its three-phase and single-phase, the Hyundai Silent Stagell Generator

is capable of powering a wide range of equipment.

The Hyundai Three-phase Silent Stagell Generator

features a direct injection system for efficiency and low fuel consumption.

The Hyundai three-phase Silent Stagell Generator is a safe and reliable product,

thanks to its "Waterproof" control panel, emergency button and IP23 protection rating.

Technical characteristics Hyundai Three-Phase Silenced Stagell Generator:

Voltage: 230/400 V

Single/three-phase

Three-phase continuous use power: 40 KVA

Nominal power: 10.7/32 Kw

Max MF/TF Power: 11.7/35 Kw

Frequency: 50 Hz

Amperage: 57.7 A

Noise level: 85 DB (at 7m)

IP Degree of Protection: IP23

Degree of Insulation: H/H

Altitude: < 1000m asl

Engine: YTO

Displacement: 3120 cc

Type of Injection: Direct

No. Cylinders: 3

Engine rpm: 1500/min

Emissions: Stage II

Consumption 100%/75%/50% of load: 6.4/4.8/3.2 l/h

Fuel: Diesel

Tank capacity: 75 L

Cooling System: Coolant

Control unit: DEEPSEA DSE6120

Total capacity of lubrication system: 14 L

Cap. total cooling system 6 L

Alternator Model: Lk184H

Exciter: Brushless - Auto - Excitation

Dimensions L x W x H: 2220 * 850 * 1150 mm

Weight: 967 kg

Preparation: ATS

If you are looking for a product similar to Hyundai Three Phase Generator click [HERE](#).

The image is purely indicative.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	11.7
Maximum power three phase (KW)	
Maximum power three phase (KVA)	30
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	TYT3A2Z-15
Emissions Regulations	Stage 2
Engine rpm (rpm)	1500
Starting system	Elettrico
Engine capacity (cm ³)	3120
Number cylinders	3
Cooling	Liquid
Alternator	LK184H
Length (mm)	
Width (mm)	850
Height (mm)	1150
Engine manufacturer	YTO
Weight (Kg)	967