



VITRIFRIGO ND35 CFS GR Refrigeration unit

Reference: G5700091.000

VITRIFRIGO ND35 CFS GR REFRIGERATION UNIT

The VITRIFRIGO ND35 CFS GR refrigeration unit represents excellence in refrigeration, offering superior performance and advanced design to meet food preservation needs in both marine and terrestrial environments.

These refrigeration units are available following compatibility verification with the vessel's dimensions and power requirements. Contact us for more information.

At the core of this unit lies the VITRIFRIGO ND35 CFS GR technology, a highly efficient system that allows maintaining refrigerator compartments up to 300 liters and freezer compartments up to 100 liters at optimal food preservation temperatures. With its versatility and reliability, the VITRIFRIGO ND35 CFS GR has become a preferred choice among boat, camper, and recreational vehicle enthusiasts seeking reliable refrigeration wherever they go.

This specific model is designed for condensation with an outboard heat exchanger, making it particularly suitable for marine applications where space is precious and energy efficiency is crucial. Thanks to its compact design and intelligent engineering, the VITRIFRIGO ND35 CFS GR unit seamlessly integrates into the surrounding environment without compromising performance.

Among the standout features of this unit is its standard equipment, including 12/24Vdc power supply without quick couplings. However, to meet diverse customer needs, additional options are available, such as power supply at 12/24Vdc - 100-240Vac 50/60Hz with quick couplings, providing greater flexibility and ease of installation.

The compact dimensions of the unit, with a width of 285 mm, a height of 160 mm, and a depth of 170 mm, make it suitable for installation in confined spaces without compromising performance. Additionally, optional extension tubes in various lengths are available to ensure easy installation and optimal operation.

In conclusion, the VITRIFRIGO ND35 CFS GR is an ideal solution for those seeking reliable performance and intelligent design in the mobile and marine refrigeration sector. With its advanced technology and high-quality construction, it ensures optimal food preservation in any environment, making it an excellent choice for travel and adventure enthusiasts.

Technical Specifications VITRIFRIGO ND35 CFS GR:

- Standard equipment: 12/24Vdc without quick couplings
- Optional equipment: 12/24Vdc - 100-240Vac 50/60Hz with quick couplings
- Width: 285 mm

- Height: 160 mm
- Depth: 170 mm

VITRIFRIGO ND35 CFS GR

Looking for a product with different technical features? [Here](#) you can find the section dedicated to VITRIFRIGO refrigerating units or other specialized brands.

For more technical information, please refer to the attached datasheet.

Images are for illustration purposes only.

Technical Sheet

Length (mm)	170
Width (mm)	285
Height (mm)	160
Product type	Unità refrigerante
Standard equipment	12/24Vdc without quick couplings
Optional equipment	12/24Vdc - 100-240Vac 50/60Hz with quick couplings