



## GENERATING SET 1020KVA

Reference: 1020KVA

### Three-phase 1020KVA generator

#### Technical characteristics of the generator:

Phase type: Three-phase  
Maximum three-phase power: 897,6 KW / 1122 KVA  
Three-phase continuous power: 816 KW / 1020 KVA  
Fuel: Diesel  
Voltage: 400 V  
Frequency: 50 Hz  
Motor: BAUDOUIN 12M26G1100/5  
Engine speed: 1500 rpm  
Starting: Electric  
Consumption: 154 Lt/h at 75% load  
Length: 5450 mm  
Width: 2200 mm  
Height: 2550 mm  
Weight: 8890 Kg  
Super-silenced

If you are looking for a similar product then you can browse the entire range of [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

#### Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	897,6
Continuous power three phase (KW)	816
Maximum power three phase (KVA)	1122
Continuous power three phase (KVA)	1020
Fuel	Diesel
Frequency (Hz)	50

Voltage (V)	400
Sockets configuration	Terminal box
Engine	BAUDOUIN 12M26G1100/5
Emissions Regulations	Stationary Use
Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Electric
Engine capacity (cm <sup>3</sup> )	31800
Number cylinders	12
Cooling	Water
Alternator	Brushless
Poles	4
Protection degree	IP44
Bore x stroke (mm)	150 x 150
Consumption (L/h)	154 at 75% of the load
Acoustic pressure	70 dB(A) at 7 m
Length (mm)	5450
Width (mm)	2200
Height (mm)	2550
Dry weight (Kg)	8890
Silenced	Yes
Super silenced	Yes
Product type	Generator
Voltage regulator	AVR
Engine manufacturer	Baudouin