



HYUNDAI GENERATOR DYNAMIC 3.5KW SINGLE-PHASE STAGE 5

Reference: 65011

Hyundai Dynamic generator 3.5kW single-phase Stage 5

Hyundai Dynamic Generator 3.5 kW Single-phase Stage 5: reliability for your needs

The Hyundai Dynamic 3.5 kW Single Phase Stage 5 Generator is a versatile and powerful model, ideal for providing power in a variety of situations. With a maximum output of 3.5 kW and a continuous output of 3.0 kW, this generator is perfect for powering tools, household appliances and lights during emergencies, DIY work or outdoor activities.

Hyunday Dynamic **Key features:**

Hyunday Dynamic 212 cc 4-stroke petrol engine: reliable and complies with Stage 5 emissions regulations.

Manual recoil start: simple and safe.

AVR voltage stabiliser: guarantees a stable and precise voltage output, protecting connected devices from voltage fluctuations.

Dual 16A sockets: for connecting several devices at the same time.

Overload indicator and low oil level indicator: for safe and reliable use.

Analogue voltmeter: for monitoring the output voltage.

12V socket: for charging batteries and powering low-voltage devices.

Reinforced anti-corrosion frame with wheels: for easy transport and longer life.

Hyunday Dynamic Generator **Advantages:**

Powerful and versatile: suitable for various applications.

Reliable and safe: with manual start-up system and integrated protections.

Easy to use and transport: thanks to wheeled chassis.

Durable: with anti-corrosion frame and alternator with copper winding.

Technical Specifications Hyundai Dynamic **3.5 kW single-phase Stage 5 generator:**

Maximum Single-phase: 3.5 KW
Single-phase continuous: 3.0 KW
Fuel: Petrol
Voltage: 230 V
Frequency: 50 HZ
Starting: Manual recoil
Autonomy 50% of load: 11h
sockets: 2X16A
Dimensions: 602x457x447 mm
Net weight: 40 Kg
Gross weight: 47 Kg
AVR
Displacement: 212 cc
Power: 7.5 HP
Noise level at 7 m: 87 dBA

If you are looking for a product with similar characteristics to HYUNDAI GENERATOR DYNAMIC click [HERE](#).

Images and technical data are purely indicative.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	3.5
Continuous power single phase (KW)	3
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	2X16A
Emissions Regulations	Stage 5
Starting system	Manual recoil
Engine capacity (cm ³)	212
Weight (Kg)	0.4