



HYUNDAI GENERATOR DYNAMIC 4KW SINGLE-PHASE STAGE 5

Reference: 65015

Hyundai Dynamic generator 4kW single-phase Stage 5

Hyundai Dynamic Generator 4kW Single-phase Stage 5: reliability for your needs

The Hyundai Dynamic 4kW Single Phase Stage 5 Generator is a versatile and powerful model, ideal for providing power in a variety of situations. With a maximum output of 4kW and a continuous output of 3.0 kW, this generator is perfect for powering tools, household appliances and lights during emergencies, DIY work or outdoor activities.

Hyundai Dynamic **Key features:**

Hyundai 212 cc 4-stroke petrol engine: powerful, reliable and complies with Stage 5 emissions regulations.

Manual recoil start: simple and safe.

AVR voltage stabiliser: guarantees a stable and precise voltage output, protecting connected devices from voltage fluctuations.

Dual 16A sockets: for connecting several devices at the same time.

Overload and low oil level warning light: for safe and reliable use.

Analogue voltmeter: for monitoring the output voltage.

12V socket: for charging batteries and powering low-voltage devices.

Reinforced anti-corrosion frame with wheels: for easy transport and longer life.

Hyundai Dynamic **Advantages:**

Powerful and versatile: suitable for various applications.

Reliable and safe: with manual start-up system and integrated protections.

Easy to use and transport: thanks to chassis with wheels.

Durable: with anti-corrosion frame and alternator with copper winding.

Technical Specifications Hyundai Dynamic 4kW single-phase Stage 5 generator:

maximum single-phase performance: 4.0 KW
Single-phase continuous performance: 3.8 KW
Fuel: Petrol
Voltage: 230 V
Frequency: 50 HZ
Starter: Manual recoil
socket: 12 V
Autonomy 50% of load: 11h
sockets: 2X16A
Dimensions: 610x480x510 mm
Net weight: 50 Kg
Gross weight: 52 Kg
AVR
Displacement: 212 cc
Engine performance : 7.5 HP
Noise level at 7 m: 87 dBA

If you are looking for a product with similar characteristics to HYUNDAI GENERATOR DYNAMIC click [HERE](#).

Images and technical data are purely indicative.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	4
Continuous power single phase (KW)	3.8
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	2X16A
Emissions Regulations	Stage 5
Starting system	Manual recoil
Engine capacity (cm ³)	212
Weight (Kg)	0.4