



Used GE Generator Set 800KVA PERKINS Single-Phase - Three-Phase

Reference: GE 800 KVA PERKINS USATO

USED GE GENERATOR SET 800KVA PERKINS SINGLE-PHASE - THREE-PHASE

Generator Set GE 800KVA PERKINS single-phase / three-phase equipped with PERKINS 3012TAG3A Diesel engine capable of delivering a maximum power of 800KVA, complete with voltage regulator.

Generator Set GE 800KVA PERKINS is compact and easy to use, equipped with soundproofed casing with panels that significantly reduce acoustic emissions, making it super-silent.

The 800KVA generator set consists of a MARELLI alternator and voltage regulator. The GE 800KVA generator set is equipped with electric start and has low fuel consumption, consuming only 127 liters per hour at 75% load for up to 7.87 hours of operation.

The GE 800KVA generator set is equipped with electric start or automatic start via ATS panel, allowing automatic start in case of blackout.

AUTOMATIC START ATS PANEL

The GE 800KVA generator set is designed for use with an automatic start ATS panel. Thanks to this, you no longer have to worry about blackouts because if the power grid goes out, this panel will automatically start the GE 800KVA, allowing you to continue your activities without losing your work data.

Technical Specifications of GE 800KVA:

Phase Type: Single-phase / Three-phase
Maximum Single-phase Power: 266 KVA / 213KW
Maximum Three-phase Power: 800 KVA / 640KW
Power Factor cos ϕ ?: 0.8
Voltage VAC: 230 / 400 V
Frequency (Hz): 50
Voltage Regulator: Yes
Starting Panel: Manual / Automatic
Engine: PERKINS 3012TAG3A
Revolutions per minute RPM: 1500
Fuel: Diesel
Tank Capacity: 1000 l
Consumption @ 75% load: 127 l/h
Autonomy @ 75% load: 7.87 h
Sound Pressure: 75 dB(A) @ 7m
Emission Regulation: Stationary Use
Length: 5500 mm

Width: 2100 mm
 Height: 2500 mm
 Net Weight: 8200 Kg

Are you looking for a used genset with different technical characteristics? View a similar product by clicking [HERE](#).

Le immagini sono puramente indicative.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	21
Maximum power single phase (KVA)	266
Maximum power three phase (KW)	640
Maximum power three phase (KVA)	800
Fuel	Diesel
Frequency (Hz)	50 / 60
Voltage (V)	230 / 400
Sockets configuration	Terminal box
Engine	PERKINS 3012TAG3A
Emissions Regulations	Stationary Use
Engine rpm (rpm)	1500
Speed governor	Mechanical
Starting system	Manual / Automatic
Cooling	Air
Alternator	Marelli
Poles	4
Fuel tank capacity (L)	100
Consumption (L/h)	127 Lt/h at 75% load
Running time (h)	7.87 h at 75% load
Length (mm)	5500
Width (mm)	2100
Height (mm)	2500
Dry weight (Kg)	8200
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS

Voltage regulator	YES
Engine manufacturer	Perkins
