

PRAMAC GBW10Y APERTO CON QUADRO COMANDO MANUALE

Reference: SH100TYAV00 /



The GBW series offers reliable and powerful machines, built for professional use in support of the power grid in case of blackouts or to serve isolated locations.

Easy to transport, install and position thanks to its compact size, this model is ideal for network emergency, construction, mobile workshops and industrial applications.

Available in open or hooded version.

YANMAR/PERKINS diesel engines

- ? Water cooling
- ? Industrial silencer
- ? Fork base with trolleys
- ? Motor fluids and charged battery
- ? MCP manual cabinet supplied as standard with 5 sockets.

The pictures are purely indicative.

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	7.47
Continuous power three phase (KW)	6.81
Maximum power three phase (KVA)	9.34
Continuous power three phase (KVA)	8.51
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Sockets configuration	1 x 400V 32A 3P+N+T CEE - 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO
Emissions Regulations	Stage 5
Speed governor	Mechanical
Starting system	Electric

Engine capacity (cm ³)	1116
Number cylinders	3
Cylinders' position	In line
Oil capacity (L)	3.5
Cooling	Water
Alternator	Linz E1S13SB , with brushes
Poles	4
Fuel tank capacity (L)	51
Consumption (L/h)	2 at 75% of the load / 2.6 at 100% of the load
Running time (h)	25.6 at 75% of the load / 19.2 at 100% of the load
Length (mm)	1600
Width (mm)	870
Height (mm)	875
Dry weight (Kg)	250
Silenced	No
Super silenced	No
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	Compound
Engine manufacturer	Yanmar