

PRAMAC GBW15P APERTO CON QUADRO COMANDO AUTOMATICO

Reference: SH130TPAU02 /



The GBW series offers reliable and powerful machines, built for professional use in support of the power grid in case of blackouts or to serve isolated locations.
 Easy to transport, install and position thanks to its compact size, this model is ideal for network emergency, construction, mobile workshops and industrial applications.
 Available in open or hooded version.

- YANMAR/PERKINS diesel engines
- Water cooling
- Industrial silencer
- Fork base with trolleys
- Motor fluids and charged battery

The images are purely indicative.

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	11.28
Continuous power three phase (KW)	10.18
Maximum power three phase (KVA)	14.1
Continuous power three phase (KVA)	12.72
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Sockets configuration	1 x 400V 32A 3P+N+T CEE
Engine	PERKINS 403D-15G, naturally aspirated
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm ³)	1496
Number cylinders	3

Cylinders' position	In line
Oil capacity (L)	6
Cooling	Water
Alternator	Linz E1S13MD, with brushes
Poles	4
Fuel tank capacity (L)	51
Consumption (L/h)	2.7 at 75% of the load / 3.6 at 100% of the load
Running time (h)	18.6 at 75% of the load / 14.2 at 100% of the load
Length (mm)	1600
Width (mm)	870
Height (mm)	950
Dry weight (Kg)	390
Silenced	No
Super silenced	No
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	Compound
Engine manufacturer	Perkins