

## PRAMAC GBW15Y APERTO CON QUADRO COMANDO AUTOMATICO

Reference: SH130TYAK02 /



Motore Diesel. Raffreddamento ad acqua. Silenziatore industriale. Base forcabile con carrelli. Liquidi motore e batteria carica. Quadro manuale MCP fornito di serie con 5 prese

L'immagine è puramente indicativa

### Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	11.44
Continuous power three phase (KW)	10.4
Maximum power three phase (KVA)	14.3
Continuous power three phase (KVA)	13
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Sockets configuration	1 x 400V 32A 3P+N+T CEE
Engine	Yanmar 3TNV88-BGPGE, naturally aspirated
Emissions Regulations	Stage 5
Engine rpm (rpm)	1500
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm <sup>3</sup> )	1642
Number cylinders	3
Cylinders' position	In line

Oil capacity (L)	6.9
Cooling	Water
Alternator	Linz E1S13MD, with brushes
Poles	4
Fuel tank capacity (L)	51
Consumption (L/h)	2.8 at 75% of the load / 3.8 at 100% of the load
Running time (h)	18 at 75% of the load / 13.5 at 100% of the load
Length (mm)	1600
Width (mm)	870
Height (mm)	950
Dry weight (Kg)	390
Silenced	No
Super silenced	No
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	Compound
Engine manufacturer	Yanmar