

PRAMAC GBW45Y APERTO CON QUADRO COMANDO AUTOMATICO

Reference: SH450TYAI02 /



Motore Diesel. Raffreddamento ad acqua. Silenziatore industriale. Base forcabile con carrelli. Liquidi motore e batteria carica. Quadro manuale MCP fornito di serie con 5 prese

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	36.68
Continuous power three phase (KW)	34.82
Maximum power three phase (KVA)	45.85
Continuous power three phase (KVA)	43.52
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Sockets configuration	1 x 400V 32A 3P+N+T CEE
Engine	Yanmar 4TNV98T-GPGE, turbocharged
Emissions Regulations	Stage 2
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm ³)	3319
Number cylinders	4
Cylinders' position	In line
Oil capacity (L)	10.5
Cooling	Water
Alternator	Mecc Alte ECO/P32-3S/4, brushless
Poles	4

Fuel tank capacity (L)	51
Consumption (L/h)	8.2 at 75% of the load / 10.9 at 100% of the load
Running time (h)	6.2 at 75% of the load / 4.7 at 100% of the load
Length (mm)	2000
Width (mm)	920
Height (mm)	1100
Dry weight (Kg)	611
Silenced	No
Super silenced	No
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Yanmar