

## PRAMAC GSL42D COFANATO CON QUADRO COMANDO AUTOMATICO

Reference: SU390TDAP02 /



Motore Diesel. Predisposto per Biodiesel. Raffreddamento ad olio con radiatore. Silenziatore industriale. Base forcabile con carrelli. Liquidi motore e batteria carica

### Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	35.62
Continuous power three phase (KW)	33.85
Maximum power three phase (KVA)	44.52
Continuous power three phase (KVA)	42.31
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Sockets configuration	1 x 400V 63A 3P+N+T CEE
Engine	Deutz AG BF4M2011, turbo
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm <sup>3</sup> )	3110
Number cylinders	4
Cylinders' position	In line
Oil capacity (L)	10
Cooling	Oil
Alternator	Mecc Alte ECO/P32-3S/4, brushless
Poles	4
Fuel tank capacity (L)	68

Consumption (L/h)	8.1 at 75% of the load / 11.2 at 100% of the load
Running time (h)	8.4 at 75% of the load / 6 at 100% of the load
Acoustic power	89 dB(A)
Acoustic pressure	60 dB(A) at 7 m
Length (mm)	2000
Width (mm)	920
Height (mm)	1310
Dry weight (Kg)	824
Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Deutz