



PRAMAC GSL65D

Reference: SG610TDAU02 /

Motore Diesel. Predisposto per Biodiesel. Raffreddamento ad olio con radiatore. Silenziatore industriale. Base forcabile con carrelli. Liquidi motore e batteria carica

Technical Sheet

| | |
|------------------------------------|---|
| Phase | Three phase |
| Maximum power three phase (KW) | 48.76 |
| Continuous power three phase (KW) | 46.23 |
| Maximum power three phase (KVA) | 60.95 |
| Continuous power three phase (KVA) | 57.79 |
| Fuel | Diesel |
| Frequency (Hz) | 50 |
| Voltage (V) | 400 |
| Engine | Deutz AG BF4M2011C, turbo intercooled |
| Speed governor | Mechanical |
| Starting system | Electric |
| Engine capacity (cm ³) | 3110 |
| Number cylinders | 4 |
| Cylinders' position | In line |
| Oil capacity (L) | 10 |
| Cooling | Oil |
| Alternator | Mecc Alte ECO/P32-2L/4, brushless |
| Poles | 4 |
| Fuel tank capacity (L) | 91 |
| Consumption (L/h) | 9.9 at 75% of the load / 13.4 at 100% of the load |

| | |
|---------------------|--|
| Running time (h) | 9.2 at 75% of the load / 6.8 at 100% of the load |
| Length (mm) | 2007 |
| Width (mm) | 758 |
| Height (mm) | 1841 |
| Dry weight (Kg) | 858 |
| Silenced | No |
| Super silenced | No |
| ATS Switch device | Optional ATS |
| Voltage regulator | AVR |
| Engine manufacturer | Deutz |