Man.El.Service Srl
Torino: +39 011 25 35 33 | Milano: +39 02 83 62 30 79
info@manelservice.com
Via Carlo Pittara 46 - 10151 Torino (TO) - Italy
PIVA 09031950018 - Num. REA: 1020262
SDI 5RUO82D Cap. Soc. € 20.000 I.V

Osmosea Water Softener ElephantineX2B Water Softener 1000LT

Reference: A-0000002553

Osmosea ElefantinoX2B Water Softener 1000LT

Osmosea Elefantino X2B is an innovative system designed specifically for softening water aboard medium and large yachts. Thanks to its compact size and duplex system, this water softener ensures a continuous supply of soft, lime-free water.

How does Osmosea Softener ElefantinoX2B work ?

The heart of Elefantino X2B is the duplex system, which allows one column to be always running while the other is in regeneration. This means you will always have soft water available, with no interruption in service.

Always soft water: Eliminates limescale, thus protecting water systems and ensuring water that is more pleasant to drink.

Continuous operation: Thanks to the duplex system, you always have fresh water available.

Compact and powerful: Despite its small size, it offers high performance.

Low power consumption: It operates on 230VAC voltage and draws only 9.5W.

Easy to install: Designed for quick and easy on-board installation.

Technical specifications ElefantinoX2B water softener :

MODEL Elefantino X2B
Production 1000 LT
Volt Continuous 230VAC
Absorption 9.5 W
Salt consumption per regeneration (kg): 4
Salt vat volume (l): 75
Connections in / out: 1"
Power supply: 230V-50Hz
Resin columns: 61 x 35 x 110 cm
Salt vat: 31 x 31 x 89 cm

Looking for a Osmosea similar product but with different characteristics? HERE you can find the area dedicated to purifiers or other brands similar to Osmosea.

Non-binding images and technical data.

Man.El.Service Srl
Torino: +39 011 25 35 33 I Milano: +39 02 83 62 30 79
info@manelservice.com
Via Carlo Pittara 46 - 10151 Torino (TO) - Italy
PIVA 09031950018 - Num. REA: 1020262
SDI 5RUO82D Cap. Soc. € 20.000 I.V

Technical Sheet

Product dimensions (mm)	920x110x350
Power consumption (W)	9.5
Capacity (Lt/h)	1000
Output voltage (VAC)	230