Man.El.Service Srl
Torino: +39 011 25 35 33 I Milano: +39 02 83 62 30 79
info@manelservice.com
Via Carlo Pittara 46 - 10151 Torino (TO) - Italy
PIVA 09031950018 - Num. REA: 1020262
SDI 5RUO82D Cap. Soc. € 20.000 I.V

PRAMAC GSW110I APERTO CON QUADRO COMANDO MANUALE

Reference: SG101TCAX00 /

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	88.7
Continuous power three phase (KW)	80.67
Maximum power three phase (KVA)	110.87
Continuous power three phase (KVA)	100.84
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	FPT NEF45TM2A, turbo aftercooler
Emissions Regulations	Stage 2
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm^3)	4500
Number cylinders	4
Cylinders' position	In line
Oil capacity (L)	12.8
Cooling	Water
Alternator	Mecc Alte ECP34-2S/4, brushless
Poles	4
Fuel tank capacity (L)	240
Consumption (L/h)	16.3 at 75% of the load / 22.1 at 100% of the load

Man.El.Service Srl
Torino: +39 011 25 35 33 I Milano: +39 02 83 62 30 79
info@manelservice.com
Via Carlo Pittara 46 - 10151 Torino (TO) - Italy
PIVA 09031950018 - Num. REA: 1020262
SDI 5RUO82D Cap. Soc. € 20.000 I.V

Running time (h)	14.7 at 75% of the load / 10.9 at 100% of the load
Length (mm)	2200
Width (mm)	1000
Height (mm)	1743
Dry weight (Kg)	1310
Silenced	No
Super silenced	No
ATS Switch device	No ATS
Voltage regulator	AVR
Engine manufacturer	FPT Iveco