

PRAMAC GSW110P APERTO CON QUADRO COMANDO MANUALE



Reference: SG101TPAY00 /

Technical Sheet

| | |
|------------------------------------|--|
| Phase | Three phase |
| Maximum power three phase (KW) | 91.74 |
| Continuous power three phase (KW) | 83.07 |
| Maximum power three phase (KVA) | 114.67 |
| Continuous power three phase (KVA) | 103.84 |
| Fuel | Diesel |
| Frequency (Hz) | 50 |
| Voltage (V) | 400 |
| Engine | PERKINS 1104C-44TAG2, turbocharged |
| Emissions Regulations | Stage 2 |
| Speed governor | Electronic |
| Starting system | Electric |
| Engine capacity (cm ³) | 4410 |
| Number cylinders | 4 |
| Cylinders' position | In line |
| Oil capacity (L) | 8 |
| Cooling | Water |
| Alternator | Mecc Alte ECP34-2S/4, brushless |
| Poles | 4 |
| Fuel tank capacity (L) | 240 |
| Consumption (L/h) | 18 at 75% of the load / 22.6 at 100% of the load |

| | |
|---------------------|--|
| Running time (h) | 13.3 at 75% of the load / 10.6 at 100% of the load |
| Length (mm) | 2200 |
| Width (mm) | 1000 |
| Height (mm) | 1743 |
| Dry weight (Kg) | 1170 |
| Silenced | No |
| Super silenced | No |
| ATS Switch device | No ATS |
| Voltage regulator | AVR |
| Engine manufacturer | Perkins |