



Master Spray GT 4.0 Electric Diaphragm Pump

Reference: 25609

Master Spray GT 4.0: Precision and Efficiency for Every Project

The Master Spray GT 4.0 is an electric diaphragm airless pump designed to meet the needs of professionals and hobbyists in the painting industry. Compact, powerful and easy to use, this machine is ideal for a wide range of applications, from construction to crafts.

Key Features:

Airless Technology: Ensures even, splash-free application of paints, lacquers, enamels and other products.

Class H electric motor: Powerful and reliable, ensuring consistent performance even under severe working conditions.

Safety: The automatic safety system shuts down the equipment if electrical safety limits are exceeded.

Durability: Stainless steel head and tungsten carbide valves guarantee a long service life.

Versatility: Suitable for a wide range of materials and applications, both indoor and outdoor.

Ease of use: Lightweight and easy to handle, it can be easily transported and used.

Standard equipment set-up includes:

HP hose dia. 1/4" - mt. 10

Gravity tank

Airless Gun

Self-cleaning nozzle cpl.

Technical specifications Master Spray GT 4.0:

voltage: 230 V

frequency: 50 Hz

Power: 1 HP

Max. flow rate L/min: 3,9

Max. flow rate w/nozzle: 2.3

Max. nozzle: 0.019"

Max. Working Pressure Bar (PSI): 200(2900)
Max. Tube Length: 60
Max. Tube Elevation: 60
Weight (naked): 19 Kg

If you are looking for a product with different characteristics [CLICK HERE](#).

Images are purely indicative.

Technical Sheet

Frequency (Hz)	50
Voltage (V)	230
Maximum output capacity (Lt/min)	3.9
Pressure (bars)	200
Mechanical power (hp)	1
Dry weight (Kg)	19
Type of pumping group	Membrane
Type of injection	Standard
Tube Elevation	60