



RIBIMEX Variable displacement pump Pro 7200 I/h

Reference: PRMCA4AUTOV

RIBIMEX Variable displacement pump Pro 7200 I/h

RIBIMEX Variable displacement pump Pro 7200 I/h: Efficiency and power for every need

The RIBIMEX Pro 7200 I/h variable displacement pump is an innovative and high-performance solution for pumping water. Thanks to its advanced technology and AISI 304 stainless steel construction, this pump guarantees reliability and durability, even under heavy-duty conditions.

Main features:

Adjustable flow rate: Thanks to the digital press-control, the pump automatically adapts the flow rate and pressure according to requirements, ensuring energy savings and greater efficiency.

Self-priming: Sucks water from a depth of up to 7 metres, making it ideal for applications such as watering gardens, filling cisterns and transferring liquids.

Powerful and versatile: With a maximum flow rate of 7200 I/h and a head of 45 metres, it can cope with a wide range of applications.

Robust construction: The AISI 304 stainless steel body and 4 stainless steel turbines guarantee corrosion resistance and a long service life.

Easy to use: The digital control panel is intuitive and makes it easy to set the different functions.

Advantages:

Energy efficiency: Automatically adapts the flow rate according to requirements, reducing consumption.

Versatility: Ideal for multiple applications, both domestic and professional.

Reliability: Built with high quality materials for long life.

Easy to use: The digital control panel is intuitive.

Quiet: Ensures quiet operation.

TENIC FEATURES:

Self-priming multi-cell surface pump
Automatic adjustment of
flow rate and pressure adjustable in the
digital keypad.
Digital Press-Control ensuring the function
on/off function of the pump and the
switch off in the event of a water shortage.
of water. Autonomous and intelligent, it calibrates
intensity of the pump, guaranteeing energy savings.
energy saving.
Power 1 300 W.
Electric cable 1.3 m.
4 AISI 304 stainless steel turbines included.
Max. flow rate 7 200 l/h.
Suction 0 to 120 L/mn min.
Max. immersion depth 7 m. Head: 45 m.
Inlet thread 1" ¼.
Outlet thread 1".
Pressure: min 1,3 bar, max 4,5 bar.
2L reservoir.
Stainless steel body.

Are you looking for a motorpump with different features? [Here you can find](#) the full range of motor pumps RIBIMEX and other specialized brands.

Images and technical data are not binding.

Technical Sheet

Power (W)	1300
Maximum use depth (m)	7
Tank capacity (L)	2
Capacity (Lt/h)	7200
Inducton system	at 0 to 120 L/mn
Maximum pressure (Bar)	4,5 bar
Pump body	Inox