Man.El.Service Srl
Torino: +39 011 25 35 33 I Milano: +39 02 83 62 30 79
info@manelservice.com
Via Carlo Pittara 46 - 10151 Torino (TO) - Italy
PIVA 09031950018 - Num. REA: 1020262
SDI 5RUO82D Cap. Soc. € 20.000 I.V

PRAMAC GSW15P HOOD WITH AUTOMATIC CONTROL PANEL

Reference: SU130TPAW02

PRAMAC GSW15P ACP Three-Phase 11.4 KW Super-Silent Generator with AVR

PRAMAC GSW15P three-phase generator with 11.4 KW output powered by a diesel engine running at 1500 RPM. The PRAMAC GSW15P generator features electric start. The three-phase alternator of the PRAMAC GSW15P generator is a brushless Mecc Alte with an AVR voltage regulator. The Perkins diesel engine makes the GSW15P generator highly reliable as it is built and designed using high-quality materials and has a base that is easily forkable for transport with trolleys.

Thanks to its casing, this generator is super-silent. Moreover, it is easy to transport, install, and position due to its compact size, making this model ideal for network emergency, construction, mobile workshops, and industrial applications. The PRAMAC GSW15P three-phase generator is suitable for outdoor use at construction sites or for small professional outdoor tasks.

Technical specifications of the PRAMAC GSW15P ACP Three-Phase Generator:

Maximum Three-Phase Power: 11.45 KW
Continuous Use Three-Phase Power: 10.33 KW
Fuel: Diesel
Voltage: 400 V
Frequency: 50 Hz
Engine: Perkins 403D-15G
Start: Electric
Consumption: 3.6 Lt/h at 100% load
Length: 1800 mm
Width: 850 mm
Height: 1260 mm
Weight: 745 Kg
AVR

Automatic Control Panel ACP:

Integrated panel connected to the generator, with a microprocessor control module that gathers all the electronic control, monitoring, and signaling circuits. Direct switching control terminal block (ACP)

N.1 3P+N+T 400V 32A

The PRAMAC GSW15P power generator is a professional diesel generator developed by Pramac that offers many solutions for a variety of applications, from continuous use to emergency network use. The PRAMAC GSW15P power generator complies with safety and noise emission regulations and can be used in both residential and industrial environments.

Man.El.Service Srl
Torino: +39 011 25 35 33 I Milano: +39 02 83 62 30 79
info@manelservice.com
Via Carlo Pittara 46 - 10151 Torino (TO) - Italy
PIVA 09031950018 - Num. REA: 1020262
SDI 5RUO82D Cap. Soc. € 20.000 I.V

The GSW15P generator is equipped with a reliable diesel-powered Perkins engine, and various control panel solutions, supplements, and accessories make it versatile and capable of meeting the most demanding customer needs.

If you are looking for a generator like the GSW15P ACP three-phase power generator, we recommend browsing our catalog of land generators to find the one that best suits your needs.

Images and technical data are non-binding.

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	11.45
Continuous power three phase (KW)	10.33
Maximum power three phase (KVA)	14.31
Continuous power three phase (KVA)	12.91
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Sockets configuration	1 x 400V 32A 3P+N+T CEE
Engine	PERKINS 403D-15G, naturally aspirated
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm^3)	1496
Number cylinders	3
Cylinders' position	In line
Oil capacity (L)	6
Cooling	Water
Alternator	Mecc Alte ECP3-2L, brushless
Poles	4
Fuel tank capacity (L)	68
Consumption (L/h)	2.7 at 75% of the load / 3.6 at 100% of the load
Running time (h)	24.8 at 75% of the load / 18.9 at 100% of the load
Acoustic power	87 dB(A)
Acoustic pressure	58 dB(A) at 7 m
Length (mm)	1800
Width (mm)	850
Height (mm)	1260
Dry weight (Kg)	745

Man.El.Service Srl
Torino: +39 011 25 35 33 I Milano: +39 02 83 62 30 79
info@manelservice.com
Via Carlo Pittara 46 - 10151 Torino (TO) - Italy
PIVA 09031950018 - Num. REA: 1020262
SDI 5RUO82D Cap. Soc. € 20.000 I.V

Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Perkins