



## WEBASTO BLUECOOL S-20 CLIMATIZZATORE NAUTICO MONOBLOCCO 20000 BTU/h

Reference: WBCL120005E

### WEBASTO BLUECOOL S-20 SINGLE-BLOCK NAUTICAL AIR CONDITIONER 20000 BTU/h

Webasto BlueCool S-20 is a nautical air conditioner in a monoblock unit suitable for use on boats, with a rated cooling capacity of 27000 BTU/h.

The Webasto BlueCool S-20 is a nautical air conditioner designed to provide an effective and reliable solution for indoor boat air conditioning. With its cooling capacity, the air conditioner ensures optimal comfort in all weather conditions.

The BlueCool S-20 is constructed from materials that are resistant to UV rays and marine corrosion in order to ensure durability. Its compactness, light weight and ease of use make it an ideal option for boats seeking a comfortable climate and high energy efficiency.

The Webasto BlueCool S-20 marine air conditioner is the ideal way to keep ambient air cool and clean on boats, thanks to advanced technology designed to deliver reliable performance over time. The system features low noise levels, thanks to noise-dampening technology that minimizes vibration during operation, and a unit design that uses specially selected high-quality materials to ensure long life.

The Webasto BlueCool S-20 uses environmentally friendly refrigerant R410A, which features low greenhouse gas emissions and meets international environmental standards. This makes it a sustainable choice for those who want a high-quality, environmentally friendly air conditioning system.

#### **The Webasto BlueCool S-20 comes complete with:**

Including external Arias temperature probe

Control panel with plate

Air filter

Air conditioning unit

Installation/instruction manual

Control box

Stops/Fasteners

Cabin thermosensor

Cable for control panel

## TECHNICAL CHARACTERISTICS WEBASTO BLUECOOL S-20

Phase type: Single-phase

Frequency (Hz): 50 / 60

Voltage (V): 230

Length (mm): 590

Width (mm): 340

Height (mm): 370

Weight (kg): 34

Cooling Power: 20,000 BTU/h / 5900 W

Absorbed current (A): 5.9/8.9 (230 V) (A)

Air Flow (free blowing) (230 V) (m<sup>3</sup>/h, cfm): 625 / 368

Product type: Air conditioner

Refrigerant: R410A

Voltage: 230V

Current consumption Maximum peak start (230 V) (A): 60

Refrigerant quantity (g): 520

Looking for a product with different technical characteristics? [Here](#) you can find the area dedicated to nautical air conditioners WEBASTO or other specialized brands.

Images and technical data are not binding.

### Technical Sheet

Phase	Single phase
Frequency (Hz)	50 / 60
Voltage (V)	230
Refrigerating yield	20.000 BTU/h / 5900 W
Length (mm)	590
Width (mm)	340
Height (mm)	370
Product type	Air conditioner
Refrigerant quantity (g)	520

---

Coolant	R410A
Weight (Kg)	34
Voltaggio	230V
Absorbed current (A)	5.9/8.9 (230 V) (A)
Air flow (free blowing) (230 V) (m <sup>3</sup> / h, cfm)	625 / 368
Current draw Start max. peak (230 V) (A)	60

---