



MOSA MPA50K Motor Pump for Dark Water 480L/min

Reference: C5200000

MOSA MPA50K Mud Water Pump 480L/min

MOSA MPA50K Mud Water Pump 480L/min: The ideal solution for dirty water and heavy-duty applications

The MOSA MPA50K Mud Water Pump 480L/min is a powerful gasoline engine pump designed for draining dirty water. Thanks to its robust construction and high performance, it is the ideal choice for professionals and individuals who need a reliable and durable pump for demanding applications.

High Performance:

Powerful engine: The KOSHIN K210 4.4 kW gasoline engine (continuous rated power) guarantees high performance and easy starting thanks to the recoil start.

High flow rate: The MOSA MPA50K is capable of sucking up to 480 liters per minute, allowing you to quickly complete even the most demanding jobs.

High head: The pump offers a total head of 90 meters, allowing you to lift water even at great heights.

Effective suction: The maximum suction lift of 8 meters allows you to suck water even from deep wells or tanks.

Technical Characteristics MOSA MPC80H:

Connection diameter Suction: 50 mm (2 in)
Connection thread: BSP pipe external thread
Delivery volume: 480 L/min
Max. suction lift: 8 m
Engine: KOSHIN K210 high rotation
Engine type: 4-stroke air-cooled gasoline engine
Displacement (cm³): 212
Continuous rated power: 4.4 kW
Max. rated power: 4.9 kW
Engine speed (rpm): 4,000
Fuel tank capacity (L): 3.3
Operating time: Approximately 1.2 hours
Starting: Recoil
Viscosity: Clear water
Net weight (kg): 33.9
Product dimensions (mm): 550 x 437 x 457 mm

Fuel: Gasoline
Total head (m): 90
Connection diameter - Discharge: 50 mm (2 in) / 25 mm (1 in)×2

If you are looking for a product with similar characteristics [CLICK HERE](#).
Images and technical data are purely indicative.

Technical Sheet

Fuel	Gasoline
Engine	KOSHIN K210 high rotation
Engine rpm (rpm)	4.000
Starting system	Pull starter
Engine capacity (cm ³)	212
Nominal power continuous	4.4 kW
Product dimensions (mm)	550 x 437 x 457
Total head (m)	90
Fuel tank capacity (L)	3.3
Net weight kg	33.9
connection diameter	Suction: 50 mm (2 in)
Connection thread	BSP external pipe thread
delivery volume	480 L/min
Maximum suction head	8 m
Motor type	Air-cooled 4-stroke petrol engine
Max Rated Power	4.9 kW
tempo di funzionamento	approx. 1.2 hours
Viscosity	Clear water
Connection diameter - Drain	50 mm (2 in) / 25 mm (1 in)×2