



MOSA MPA50H Motopump for dark water 500L/min

Reference: C5600000

MOSA MPA50H Mud Water Pump 500L/min

The MOSA MPA50H is a high-quality motor pump designed for draining dirty water. Thanks to its robust structure and powerful Honda GX200 engine. The MOSA MPA50H is the ideal choice for those looking for a powerful, reliable, and versatile mud water pump. Thanks to its advanced technical features, it can meet the needs of individuals, professionals, and farms.

Main Features MOSA MPA50H:

Powerful Engine: The Honda GX200 4-stroke petrol engine ensures high performance and reliability.

High Flow Rate: The MOSA MPA50H offers a maximum flow rate of 500 liters per minute, allowing you to quickly complete even the most demanding tasks.

High Head: The pump can lift water up to 90 meters high, making it suitable for various applications.

Effective Suction: The maximum suction lift of 8 meters allows you to draw water even from deep wells or tanks.

Versatile: The MOSA MPA50H can be used for various applications, including:

Draining dirty water from construction sites, ditches, ponds, and swimming pools.

Irrigation of fields and gardens, and much more!

Technical Specifications MOSA MPA50H:

Suction connection diameter: 50 mm (2 inches)
Connection thread: BSP pipe external thread
Delivery volume: 500 L/min
Maximum suction lift: 8 m
Engine: Honda GX200 high speed
Engine type: 4-stroke air-cooled forced air gasoline engine
Displacement: 196 cm³
Continuous rated power: 3.7 kW
Maximum rated power: 4.6 kW
Engine speed: 3,600 rpm
Fuel tank capacity: 3.1 liters
Operating time: Approximately 1.5 hours

Starting: Recoil
Viscosity: Clear water
Net weight: 34.6 kg
Dimensions: 550 x 437 x 457 mm
Fuel: Gasoline
Total head: 90 m
Discharge connection diameter: 50 mm (2 inches) / 25 mm (1 inch) x 2

If you are looking for a product with similar features [CLICK HERE](#).
Images and technical data are purely indicative.

Technical Sheet

Fuel	Gasoline
Engine	HONDA GX200 high rotation
Engine rpm (rpm)	3.600
Starting system	Pull starter
Engine capacity (cm ³)	196
Nominal power continuous	3.7 kW
Product dimensions (mm)	550 x 437 x 457
Total head (m)	90
Fuel tank capacity (L)	3.1
Net weight kg	34,6
connection diameter	Suction: 50 mm (2 in)
Connection thread	BSP external pipe thread
delivery volume	500 L/min
Maximum suction head	8 m
Motor type	Air-cooled 4-stroke petrol engine
Max Rated Power	4.6 kW
tempo di funzionamento	approx. 1.5 hours
Viscosity	Clear water
Connection diameter - Drain	50 mm (2 in) / 25 mm (1 in) x 2