



## MOSA GC5360HBM Generator with Integrated Compressor 4.6KW 230V 9.5 bar

Reference: CB100010

### MOSA GC5360 HBM Generator with Integrated Compressor 4.6KW 230V 9.5 bar

The **MOSA GC5360 HBM Generator with Integrated Compressor 4.6KW 230V 9.5bar** is a powerful and versatile solution for those who need both electrical power and compressed air in a single machine. This single-phase generator, powered by gasoline, delivers a power of 4.6KW at 230V and 50Hz, ideal for powering electrical tools and equipment in various contexts, from construction sites to maintenance activities.

The heart of the **MOSA GC5360 HBM** is the Honda GX270 engine, a 270cm<sup>3</sup> single-cylinder air-cooled engine, which ensures reliability and high performance. The starting is both manual and electric, offering flexibility in different situations. With a fuel tank capacity of 5.3 liters, the generator ensures adequate autonomy for work needs.

A distinctive feature of this model is the integrated compressor with a 10-liter aluminum tank. The compressor provides a maximum pressure of 9.5 bar and a suction capacity of 360 l/min, making it suitable for using pneumatic tools such as nailers, screwdrivers, and spray guns. The safety valve is calibrated at 11 bar, ensuring safety during use.

The **MOSA GC5360 HBM Generator with Integrated Compressor 4.6KW 230V 9.5bar** is designed to be robust and durable, with an IP44 protection rating. The product dimensions are 980 x 610 x 685 mm and the dry weight is 158 kg, facilitating transport and positioning. The noise level at 7 meters is 95 LWA (71 dB(A)), a contained value for a generator of this power.

#### Technical Features MOSA GC5360 HBM Generator with Integrated Compressor:

Phase type: Single phase

Single-phase power (KW): 4.6

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230

Engine: Honda GX270

Engine speed (rpm): 3000

Start: Manual / Electric

Displacement (cm<sup>3</sup>): 270

Number of cylinders: 1

Cooling: Air

Fuel tank capacity (L): 5.3

Dry weight (Kg): 158

Compressor tank capacity: 10lt (Aluminum)

Product dimensions (mm): 980 x 610 x 685

Protection degree: IP44

Noise level at 7 mt: 95 LWA (71 dB(A) - 7 m)

Available power: 4.4 KVA / 3.9 KWP

Max pressure (bar): 9.5

Safety valve calibration pressure: 11 bar

Suction capacity: 360 l/min

Looking for a generator with different technical features? [HERE](#) you can find the area dedicated to MOSA generators or other specialized brands.

Images and technical data are not binding.

## Technical Sheet

Phase	Single phase
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Engine	HONDA GX270
Engine rpm (rpm)	3000
Starting system	Manual / Electric
Engine capacity (cm <sup>3</sup> )	270
Number cylinders	1
Cooling	Air
Single-phase power (KW)	4.6
Protection degree	IP44
Product dimensions (mm)	980 x 610 x 685
Fuel tank capacity (L)	5.3
Consumption (L/h)	1.8 l/h at 75% load
Dry weight (Kg)	158
Noise level at 7 m	95 LWA (71 dB(A) - 7 m)

---

Tank capacity Compressor	10lt (Aluminum)
Withdrawable Power	4,4 KVA / 3,9 KW
Max pressure (bar)	9.5
Pressure setting safety valve	11 bar
Suction flow rate	360 l/min

---