



MOSA GC7360HBM Generator with Integrated Compressor 6.4KW 230V 9.5 bar

Reference: CB200011

MOSA GC7360HBM Generator with Integrated Compressor 6.4KW 230V 9.5 bar

The MOSA **Generator with Integrated Compressor GC7360HBM 6.4KW 230V 9.5 bar** is a powerful and reliable solution for those who need both electricity and compressed air in a single machine. This single-phase generator, powered by gasoline, delivers 6.4KW at 230V and 50Hz, making it ideal for professional applications in construction sites, mobile workshops, and maintenance activities.

The heart of the **MOSA GC7360HBM** is the Honda GX390 engine, a robust and reliable single-cylinder engine with a displacement of 390/440 cm³, air-cooled, which ensures high and lasting performance. The starting system is both manual and electric, offering flexibility in various operating situations. With a fuel tank capacity of 6.1 liters, the MOSA generator ensures extended autonomy, with a consumption of 2.5 l/h at 75% load.

A distinctive feature of this model is the integrated compressor with a 10-liter aluminum tank. The compressor provides a maximum pressure of 9.5 bar and an intake flow of 360 l/min.

Technical Features MOSA GC7360HBM:

Phase type: Single-phase
Single-phase power (KW): 6.4
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Engine: Honda GX390
Engine speed (rpm): 3000
Starting: Manual / Electric
Displacement (cm³): 390 / 440
Number of cylinders: 1
Cooling: Air
Fuel tank capacity (L): 6.1
Dry weight (Kg): 170
Compressor tank capacity: 10L (Aluminum)
Product dimensions (mm): 980 x 610 x 685
Protection degree: IP44
Noise level at 7m: 95 LWA (71 dB(A) – 7 m)
Power available: 6.5 KVA / 5.8 KWP
Maximum pressure (bar): 9.5
Pressure setting of safety valve: 11 bar
Intake flow: 360 l/min
Consumption (L/h): 2.5 l/h at 75% load

Looking for a generator with different technical features? [HERE](#) you can find the area dedicated specialized brands.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Engine	Honda GX390
Engine rpm (rpm)	3000
Starting system	Manual / Electric
Engine capacity (cm ³)	390 / 440
Number cylinders	1
Cooling	Air
Single-phase power (KW)	6.4
Protection degree	IP44
Product dimensions (mm)	980 x 610 x 685
Fuel tank capacity (L)	6.1
Consumption (L/h)	2.5 l/h at 75% load
Dry weight (Kg)	170
Noise level at 7 m	95 LWA (71 dB(A) - 7 m)
Tank capacity Compressor	10lt (Aluminum)
Withdrawable Power	6,5 KVA / 5,8 KW
Max pressure (bar)	9.5
Pressure setting safety valve	11 bar
Suction flow rate	360 l/min