



GYS BOOSTER LITHIUM NOMAD POWER PRO 24XL 24V

Reference: 025905

GYS BOOSTER LITHIUM NOMAD POWER PRO 24XL

The GYS BOOSTER LITHIUM NOMAD POWER PRO 24XL

is a multifunctional portable power solution, designed to offer high performance and versatility in various situations. It combines the ability to jump-start vehicles with dead batteries,

power electronic devices and provide emergency lighting.

Main Features:

Vehicle Booster 24V:

Jump-starts 24V vehicles with dead batteries in seconds (motorcycles, cars, SUVs, vans, tractors, boats).

Warning: Not compatible with LiFePO4 lithium batteries.

Portable Power Supply:

8 Ah capacity to power electronic devices.

2 USB 5V-2.1A ports for smartphones, tablets, GPS.

1 output port 12V-3.5A for refrigerators, fans, etc.

Built-in power bank.

Emergency Lighting:

Integrated LED lamp with 3 modes: normal, strobe, SOS.

28 high-brightness LEDs.

Advanced Safety:

Anti-spark technology.

Protection against short circuits and reverse polarity.

Protection against excessive start-up currents and overheating.

LCD Display:
Displays the battery charge percentage and the used input/output ports.

Connectivity:
USB-C and Lightning ports.

The GYS BOOSTER LITHIUM NOMAD POWER PRO 24XL is an essential tool for anyone looking for a versatile and reliable power solution, ideal for use on the road, in the workshop, or in emergency situations.

Technical Features:

Capacity per cell: 8 Ah 236.8 Wh

Full charge: 10 h

Start: 1400 A

Manual crank DC: 2400 A

Peak Battery: 3000 A

USB-C: YES

Lightning: Yes

INPUT: 18 V - 2 A

OUTPUT: 5 V - 2.1 A (x2) - 12 V 3.5A

Power bank: Yes

LED Light: Light / SOS / SPOT

Product dimensions: 278 x 110 x 274 mm

Weight (Kg): 5.6

If you are looking for a product with similar features [click HERE](#).
Images and technical data are purely indicative and may be revised by the manufacturer.

Technical Sheet

Product dimensions (mm)	278 x 110 x 274
Weight (Kg)	5.6
Capacity per cell	8 Ah 236.8 Wh
Power bank	Yes
LED light	Light / SOS / SPOT
Full charge	10 h

Start	1400 A
Crank CC	2400 A
Peak Battery	3000 A
USB-C	SI
Lightning	SI
INPUT	18 V - 2 A
OUTPUT	5 V - 2.1 A (x2) - 12 v 3.5A
