



GREEN POWER GP33S/K-SV Gruppo Elettrogeno Silenziato StageV

Reference: 261919

GREEN POWER GP33S/K-SV Silenced Generator Set StageV

GREEN POWER GP33S/K-SV Silenced Generator Set StageV is a reliable and versatile power solution, designed to provide both single-phase and three-phase power in a variety of applications. With a **maximum three-phase power of 33 KVA (30 KW)**, this generator set is capable of handling medium loads, making it ideal for commercial, industrial and emergency applications.

The heart of this generator is a **KOHLER KDI1903TCR (E)** engine, a robust and efficient diesel engine, designed to operate at 1500 rpm, ensuring stable and constant power delivery. The electric start facilitates the generator set's ignition, while the water cooling system ensures reliable operation even under high load conditions.

The **MECC ALTE ECP28-VL/4 C** alternator guarantees high-quality power production, with a voltage of 230/400V and a frequency of 50Hz, ideal for powering a wide range of electrical equipment.

The **120-liter fuel tank** offers extended autonomy, reducing the need for frequent refueling. The silenced version of the generator set keeps noise levels to a minimum, making it suitable even for noise-sensitive environments.

The **compact dimensions** (2260 x 1000 x 1420 mm) and the **dry weight of 1150 kg** facilitate installation and transport. The optional ATS (Automatic Transfer Switch) switch panel allows automatic switching to emergency power in case of power failure.

TECHNICAL FEATURES GREEN POWER GP33S/K-SV Silenced Generator Set StageV:

Phase type: Single-phase / Three-phase
Maximum three-phase power (KW): 30
Maximum three-phase power (KVA): 33
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: KOHLER KDI1903TCR (E)
Engine speed (rpm): 1500
Starting: Electric
Cooling: Water
Alternator: MECC ALTE ECP28-VL/4 C
Fuel tank capacity (L): 120
Length (mm): 2260
Width (mm): 1000
Height (mm): 1420
Dry weight (Kg): 1150
Silenced: Yes

ATS switch panel: Optional
 Emission standard: Stage 5

Looking for a generator set with different features? [HERE](#) you can find the entire range of GREEN POWER or other specialized brands.

Images and technical data are not binding. Please always refer to the technical data sheet issued by the manufacturer. Manel service does not assume responsibility for any changes made by the manufacturer.

Technical Sheet

Phase	Single phase / Three phase
Maximum power three phase (KW)	30
Maximum power three phase (KVA)	33
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	KOHLER KDI1903TCR (E)
Emissions Regulations	Stage 5
Engine rpm (rpm)	1500
Starting system	Elettrico
Cooling	Water
Alternator	MECC ALTE ECP28-VL/4 C
Fuel tank capacity (L)	120
Length (mm)	2260
Width (mm)	1000
Height (mm)	1420
Dry weight (Kg)	1150
Silenced	Yes
ATS Switch device	Optional ATS