

PRAMAC GSW10Y COFANATO CON QUADRO COMANDO MANUALE (MCP)

Reference: SU211TCAX00



Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	176
Continuous power three phase (KW)	162.22
Maximum power three phase (KVA)	220
Continuous power three phase (KVA)	202.78
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	FPT NEF67TE2A, turbo aftercooler
Speed governor	Electronic
Starting system	Electric
Engine capacity (cm ³)	6
Number cylinders	6
Cylinders' position	In line
Oil capacity (L)	17
Cooling	Water
Alternator	Mecc Alte ECO38-2SN/4, brushless
Poles	4
Fuel tank capacity (L)	350
Consumption (L/h)	33.5 at 75% of the load / 44 at 100% of the load
Running time (h)	10.4 at 75% of the load / 7.9 at 100% of the load

Acoustic power	97 dB(A)
Acoustic pressure	68 dB(A) at 7 m
Length (mm)	3400
Width (mm)	1250
Height (mm)	1770
Dry weight (Kg)	2145
Inverter	No
AVR	Yes
Compound	No
Silenced	Yes
Super silenced	Yes