

PRAMAC GSW220V COFANATO CON QUADRO COMANDO MANUALE

Reference: SU201TWAX00



Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	176
Continuous power three phase (KW)	162.14
Maximum power three phase (KVA)	220
Continuous power three phase (KVA)	202.67
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	VOLVO TAD733GE, turbo intercooled
Emissions Regulations	Stage 2
Speed governor	Electronic
Starting system	Electric
Engine capacity (cm ³)	7150
Number cylinders	6
Cylinders' position	In line
Oil capacity (L)	34
Cooling	Water
Alternator	Mecc Alte ECO38-2SN/4, brushless
Poles	4
Fuel tank capacity (L)	350
Consumption (L/h)	34.9 at 75% of the load / 46.5 at 100% of the load

Running time (h)	10 at 75% of the load / 7.5 at 100% of the load
Acoustic power	94 dB(A)
Acoustic pressure	65 dB(A) at 7 m
Length (mm)	3400
Width (mm)	1250
Height (mm)	1980
Dry weight (Kg)	2540
Silenced	Yes
Super silenced	Yes
ATS Switch device	No ATS
Voltage regulator	AVR
Engine manufacturer	Volvo