



## VINCO 60156 GENERATOR INVERTER SILENCED 2KW

Reference: 60156

### VINCO 60156 SILENCED INVERTER GENERATOR 2.0KW

The **VINCO 60156 SILENCED INVERTER GENERATOR 2.0KW** is a compact and high-performance single-phase generator, ideal for domestic, recreational and professional applications that require stable and silenced energy. Equipped with **Inverter** technology, it ensures constant and safe current supply even for sensitive electronic equipment.

Powered by a **99.2 cc** 4-stroke engine with **3 HP** power, it offers a maximum power of **2 kW** and a continuous power of **1.7 kW**, with a voltage of **230 V** and a frequency of **50 Hz**. It features manual starting and a fuel tank capacity of **4.1 liters**, ensuring a range of **3.4-3.8 hours** at full load.

The compact structure (555 × 315 × 490 mm) and a dry weight of only **18.5 kg** make it easily transportable, while the noise level of **93 dB(A)** and the silenced body ensure more discreet operation than traditional generators.

Equipped with **2 x 16A sockets**, a **Shenwei** alternator and an oil capacity of **0.5 L**, the **VINCO 60156 SILENCED INVERTER GENERATOR 2.0KW** combines efficiency, reliability and portability, making it the ideal choice for those looking for ready-to-use energy in any situation.

Technical Features:

Phase type: Single-phase

Maximum single-phase power: 2 kW

Continuous single-phase power: 1.7 kW

Frequency: 50 Hz

Voltage: 230 V

Engine: 4-stroke

Displacement: 99.2 cc

Starting: Manual

Oil capacity: 0.5 L

Fuel tank capacity: 4.1 L

Autonomy at full load: 3.4 – 3.8 h

Sound pressure: 93 dB(A)

Length: 555 mm

Width: 315 mm

Height: 490 mm

Dry weight: 18.5 kg

Silenced: Yes

Voltage regulator: Inverter

Alternator: Shenwei

Socket configuration: 2 × 16A

Power: 3 HP

Inverter: Yes

If you are looking for a product with similar technical characteristics [CLICK HERE](#).

## Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	2
Continuous power single phase (KW)	1.7
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	2X16A
Engine	4 Tempi
Starting system	Manuale
Oil capacity (L)	0.5
Alternator	Shenwei
Fuel tank capacity (L)	4.1
Running time (h)	100% load 3.4-3.8 h
Acoustic pressure	93 dB(A)
Length (mm)	555
Width (mm)	315
Height (mm)	490
Dry weight (Kg)	18.5
Inverter	Yes

---

Silenced	Yes
Voltage regulator	Inverter
protezione da sovratensione	3
displacement	99,2 cc

---