

Generator Set 710kVA Silenced 370L



Reference: NB - GE710kVA

Soundproof Generator 710kVA 370L

The Soundproof Generator 710kVA 370L is designed to provide constant and safe electrical power in any situation. Thanks to the powerful Hyundai engine and the Leroy Somer alternator, this generator guarantees high performance and operational continuity, becoming an indispensable support for companies, construction sites, and facilities requiring high power.

The super soundproof canopy minimizes acoustic impact, making the Soundproof Generator 710kVA 370L suitable not only for industrial environments but also for urban contexts or events where silence is essential. Robust, efficient, and easy to manage, it combines power and reliability in a single professional solution.

Main features – Soundproof Generator 710kVA 370L:

Three-phase maximum power: 710 KVA
Continuous three-phase power: 568 KW
Fuel: Diesel
Voltage: 230/400 V
Engine: HYUNDAI DP180LB
Fuel tank capacity: 370 L
Alternator: Leroy Somer TAL0473 F
Starting: Automatic
Length: 5000 mm
Width: 1900 mm
Height: 2350 mm
Weight: 5690 Kg

Power, efficiency and silence in a single Soundproof Generator 710kVA 370L:

The **Soundproof Generator 710kVA 370L** has been designed to ensure maximum operational continuity in every situation. The combination of the powerful Hyundai engine and the Leroy Somer alternator delivers consistent and long-lasting performance, while the super soundproof canopy drastically reduces noise, making it suitable even in environments where noise is a critical factor.

The construction quality of the Soundproof Generator 710kVA 370L is built to last: powder-coated carbon steel, class 1 sound-absorbing materials, and anti-vibration systems guarantee strength and stability even under the toughest conditions. Every detail, from reinforced access doors to integrated safety systems, has been designed to make use and maintenance easier.

Looking for a generator with different technical features? [CLICK HERE](#) to explore the section dedicated to generators from leading specialized brands.

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	568
Continuous power three phase (KW)	568
Maximum power three phase (KVA)	710
Continuous power three phase (KVA)	640
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	HYUNDAI DP180LB
Emissions Regulations	NON EMISSIONATO
Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Automatico
Engine capacity (cm ³)	18273
Number cylinders	10
Cylinders' position	In line
Cooling	Water
Alternator	Leroy Somer TAL0473 F
Poles	4
Protection degree	IP23
Fuel tank capacity (L)	370
Consumption (L/h)	103.8 Lt/h al 75% del carico
Running time (h)	3.34 h al 75% del carico
Acoustic pressure	75 dB(A) at 7 m
Length (mm)	5000
Width (mm)	1900
Height (mm)	2350
Dry weight (Kg)	5690
Silenced	Yes
Super silenced	No
ATS Switch device	Optional ATS
Lead-acid battery	2X12V 200Ah

Insulation Class

H