

PRAMAC GSW275V COFANATO CON QUADRO COMANDO AUTOMATICO

Reference: SC251TWAR04



Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	220
Continuous power three phase (KW)	201.18
Maximum power three phase (KVA)	275
Continuous power three phase (KVA)	251.48
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	VOLVO TAD734GE, turbo intercooled
Emissions Regulations	Stage 2
Speed governor	Electronic
Starting system	Electric
Engine capacity (cm ³)	7150
Number cylinders	6
Cylinders' position	In line
Oil capacity (L)	29
Cooling	Water
Alternator	Mecc Alte ECO38-1LN/4, brushless
Poles	4
Fuel tank capacity (L)	636
Consumption (L/h)	44.6 at 75% of the load / 55.1 at 100% of the load

Running time (h)	14.3 at 75% of the load / 11.5 at 100% of the load
Acoustic power	97 dB(A)
Acoustic pressure	68 dB(A) at 7 m
Length (mm)	3951
Width (mm)	1438
Height (mm)	2085
Dry weight (Kg)	2990
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Volvo