



PRAMAC GSW10Y COFANATO CON QUADRO COMANDO MANUALE (MCP)

Reference: SG271T5AZ02 /

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	248.3
Continuous power three phase (KW)	219.26
Maximum power three phase (KVA)	310.38
Continuous power three phase (KVA)	274.07
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	Doosan P126Ti, turbo intercooled
Emissions Regulations	Stage 2
Speed governor	Electronic
Starting system	Electric
Engine capacity (cm ³)	11051
Number cylinders	6
Cylinders' position	In line
Oil capacity (L)	23
Cooling	Water
Alternator	Mecc Alte ECO38-2LN/4, brushless
Poles	4
Fuel tank capacity (L)	636
Consumption (L/h)	43.9 at 75% of the load / 58.1 at 100% of the load

Running time (h)	14.5 at 75% of the load / 11 at 100% of the load
Length (mm)	3300
Width (mm)	1400
Height (mm)	1887
Dry weight (Kg)	2580
Silenced	No
Super silenced	No
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Doosan