

## PRAMAC GSW310DO COFANATO CON QUADRO COMANDO AUTOMATICO

Reference: SC271T5AZ02



### Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	248.3
Continuous power three phase (KW)	219.26
Maximum power three phase (KVA)	310.38
Continuous power three phase (KVA)	274.07
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	Doosan P126Ti, turbo intercooled
Emissions Regulations	Stage 2
Speed governor	Electronic
Starting system	Electric
Engine capacity (cm <sup>3</sup> )	11051
Number cylinders	6
Cylinders' position	In line
Oil capacity (L)	23
Cooling	Water
Alternator	Mecc Alte ECO38-2LN/4, brushless
Poles	4
Fuel tank capacity (L)	636
Consumption (L/h)	43.9 at 75% of the load / 58.1 at 100% of the load

Running time (h)	14.5 at 75% of the load / 11 at 100% of the load
Acoustic power	93 dB(A)
Acoustic pressure	68 dB(A) at 7 m
Length (mm)	3951
Width (mm)	1438
Height (mm)	2085
Dry weight (Kg)	3105
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Doosan