



PRAMAC GSW10Y COFANATO CON QUADRO COMANDO MANUALE (MCP)

Reference: SG311TWA002 /

Technical Sheet

| | |
|------------------------------------|--|
| Phase | Three phase |
| Maximum power three phase (KW) | 264 |
| Continuous power three phase (KW) | 252 |
| Maximum power three phase (KVA) | 330 |
| Continuous power three phase (KVA) | 315 |
| Fuel | Diesel |
| Frequency (Hz) | 50 |
| Voltage (V) | 400 |
| Engine | VOLVO TAD752GE, turbo intercooled |
| Emissions Regulations | Stage 2 |
| Speed governor | Electronic |
| Starting system | Electric |
| Engine capacity (cm ³) | 12780 |
| Number cylinders | 6 |
| Cylinders' position | In line |
| Oil capacity (L) | 36 |
| Cooling | Water |
| Alternator | Mecc Alte ECO38-2LN/4, brushless |
| Poles | 4 |
| Fuel tank capacity (L) | 636 |
| Consumption (L/h) | 48.5 at 75% of the load / 63.4 at 100% of the load |

| | |
|---------------------|--|
| Running time (h) | 13.1 at 75% of the load / 10 at 100% of the load |
| Length (mm) | 3300 |
| Width (mm) | 1460 |
| Height (mm) | 1965 |
| Dry weight (Kg) | 3160 |
| Silenced | No |
| Super silenced | No |
| ATS Switch device | Optional ATS |
| Voltage regulator | AVR |
| Engine manufacturer | Volvo |