

PRAMAC GSW35Y COFANATO CON QUADRO COMANDO MANUALE

Reference: SU300TYAY00 /



Technical Sheet

| | |
|------------------------------------|---|
| Phase | Three phase |
| Maximum power three phase (KW) | 26 |
| Continuous power three phase (KW) | 24.4 |
| Maximum power three phase (KVA) | 32.5 |
| Continuous power three phase (KVA) | 30.5 |
| Fuel | Diesel |
| Frequency (Hz) | 50 |
| Voltage (V) | 400 |
| Sockets configuration | 1 x 400V 63A 3P+N+T - 1 x 400V 32A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO |
| Engine | Yanmar 4TNV98-ZGPGE, naturally aspirated |
| Emissions Regulations | Stage 3A |
| Speed governor | Electronic |
| Starting system | Electric |
| Engine capacity (cm ³) | 3319 |
| Number cylinders | 4 |
| Cylinders' position | In line |
| Oil capacity (L) | 11.2 |
| Cooling | Water |
| Alternator | Mecc Alte ECP28-VL/4, brushless |
| Poles | 4 |
| Fuel tank capacity (L) | 68 |

| | |
|---------------------|---|
| Consumption (L/h) | 5.9 at 75% of the load / 7.9 at 100% of the load |
| Running time (h) | 11.5 at 75% of the load / 8.6 at 100% of the load |
| Acoustic power | 95 dB(A) |
| Acoustic pressure | 66 dB(A) at 7 m |
| Length (mm) | 2000 |
| Width (mm) | 920 |
| Height (mm) | 1310 |
| Dry weight (Kg) | 773 |
| Silenced | Yes |
| Super silenced | Yes |
| Product type | Generator |
| ATS Switch device | No ATS |
| Voltage regulator | AVR |
| Engine manufacturer | Yanmar |