



## Generator Stationary 275KVA AVR

Reference: GEA275AVR

### 275KVA AVR Stationary Generator Set

275KVA AVR Stationary Generator Set: silent and super silent diesel generator set with maximum power of 275 kVA (220 kW) and continuous power of 250 kVA (200 kW).  
6.7-liter FPT Iveco 6-cylinder in-line engine, water-cooled, with electronic speed governor at 1500 rpm;  
Stamford alternator with integrated AVR for stable voltage at 230/400 V, 50 Hz.  
Compact dimensions (3230x1140x2200 mm) and dry weight of 2498 kg,  
ideal for stationary installations in industrial or commercial environments where silence and reliability are essential. priority.

#### Technical characteristics:

**Product type:** Generator  
**Phase type:** Single-phase / Three-phase  
**Continuous power:** 250 kVA / 200 kW  
**Maximum power:** 275 kVA / 220 kW  
**Fuel:** Diesel  
**Frequency:** 50 Hz  
**Voltage:** 230 V / 400 V  
**Engine speed:** 1500 rpm  
**Speed ??governor:** Electronic  
**Displacement:** 6.70 cm<sup>3</sup> (6.7 litres)  
**Number of cylinders:** 6  
**Cooling:** Water  
**Alternator:** Stamford  
**Length:** 3230 mm  
**Width:** 1140 mm  
**Height:** 2200 mm  
**Dry weight:** 2498 kg  
**AVR:** Yes (voltage regulator included)  
**Silent:** Yes  
**Super Silenced:** Yes  
**Engine brand:** FPT Iveco  
**Emissions standard:** Stationary use

If you are looking for a similar product, click [HERE](#).

#### Technical Sheet

Phase

Single phase / Three phase

Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Emissions Regulations	Stationary Use
Engine rpm (rpm)	1500
Speed governor	Electronic
Engine capacity (cm <sup>3</sup> )	6.70
Number cylinders	6
Cooling	Water
Alternator	STAMFORD
Length (mm)	3230
Width (mm)	1140
Height (mm)	2200
Dry weight (Kg)	2498
AVR	Yes
Silenced	Yes
Super silenced	Yes
Product type	Generator
Voltage regulator	AVR
Engine manufacturer	FPT Iveco
Continuous power [kW]	200
Maximum power (KW)	220
Continuous Power (KVA)	250
Maximum Power (KVA)	275