



HYUNDAI 65148 GASOLINE GENERATOR SINGLE PHASE STAGE V INVERTER 3 KW

Reference: 65148

HYUNDAI 65148 SINGLE-PHASE STAGEV INVERTER GASOLINE GENERATOR 3 KW

The HYUNDAI 65148 is a single-phase generator equipped with a 4-stroke StageV gasoline engine that delivers a maximum power of 3.3 kW. This generator is complete with an inverter voltage regulator.

The HYUNDAI 65148 features manual start.

The HYUNDAI 65148 generator provides reliable power for home, work, and leisure environments, safely powering appliances and other electronic devices.

Extremely practical sockets and controls make starting and operating the generator extremely simple and quick.

The HYUNDAI 65148 generator has a practical handle for easy mobility and storage. The HYUNDAI 65148 has a robust structure and a tank with a maximum capacity of 7 liters.

STAGEV EMISSIONS REGULATION

The HYUNDAI 65148 is equipped with a "mobile" STAGEV engine, as required by European Regulation 2016/1628. These new engines significantly reduce particulate and nitrogen oxide emissions released by the generator into the environment, ensuring a 200% reduction in environmental impact compared to standard engines.

Technical characteristics of the HYUNDAI 65148 generator

Phase type: Single phase

Continuous power: 3 KVA / 3 KW

Maximum power: 3.3 KVA / 3.3 KW

Engine: 4-stroke

Engine speed: 3000 rpm

Emissions standard: Stage V

Starting: Manual

Fuel: Petrol

Voltage: 230 V

Frequency: 50 Hz

Socket panel: 2 x CEE 16A 230V

Tank capacity: 7 l

Sound pressure level: 66 dB(A) @ 7 m

Length: 500 mm

Width: 295 mm

Height: 490 mm

Dry weight: 21 kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the area dedicated to HYUNDAI generators or other specialized brands.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	3.3
Continuous power single phase (KW)	3
Maximum power single phase (KVA)	3.3
Continuous power single phase (KVA)	3
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Engine	4 Tempi
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Manual
Engine capacity (cm ³)	143
Alternator	Avvolgimento in rame
Fuel tank capacity (L)	7
Acoustic pressure	66 dB(A) at 7 m
Length (mm)	500
Height (mm)	490
Dry weight (Kg)	21
Silenced	Yes
Super silenced	Yes
ATS Switch device	No ATS
Voltage regulator	Inverter