



Pramac PMi6500 Inverter Generator StageV

Reference: PR552SXB000

Pramac PMi6500 StageV

Pramac PMi6500 Inverter Generator ATS Connector - StageV represents the ideal solution for those looking for a generator that combines silent operation, lower fuel consumption and voltage stability. Thanks to its inverter technology, this Pramac PMi6500 generator stabilizes the output voltage, providing safe and reliable power for all types of equipment, including the most sensitive electronic devices.

Efficiency comes first: the "Economy" mode automatically adjusts the speed of the OHV engine based on the required load, optimizing average fuel consumption and significantly reducing noise. The Pramac OHV engine guarantees constant power for various applications, while the low oil level protection ensures durability.

Pramac Technical Features PMi6500 Generator:

Frequency Hz: 50

Voltage V: 230

Phases: 1

Maximum Power Kw: 6.5

Nominal Power Kw: 6

Brand: Pramac

Type: OHV

Exhaust gas emission level: Stage V

Engine speed rpm: Variable

Fuel: Petrol

Starting system: Electric (+Recoil)

Low oil level protection (oil guard): ✓

Voltage regulation system: Inverter

Length (L) mm: 625

Width (W) mm: 448

Height (H) mm: 560

Weight (dry) kg: 50.5

Tank capacity: 14

Fuel consumption 50% l/h: 2.1

Autonomy at 50% load (Eco Mode) h: 6.6

Sound power (LWA) dBA: 96

Sound pressure at 7 m dBA: 68

Sockets: 1x SCHUKO 230V 16A IP44 + 1x 2P+T CEE 230V 32A IP44 1

If you are looking for a product with features techniques similar to Pramac Generator PMI6500 [CLICK HERE](#).

Images and technical data are not binding. Please always consult the technical data sheet issued by the manufacturer. Manel Service does not assume responsibility for any changes made by the manufacturer or any typing errors.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	6.5
Engine	PRAMAC OHV
Continuous power single phase (KW)	6
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1x230V 32A 2P+T CEE 1x230V 16A 2P+T Schuko
Emissions Regulations	Stage 5
Engine rpm (rpm)	Variabile
Starting system	Elettrico (+Strappo)
Oil capacity (L)	0.85
Fuel tank capacity (L)	14
Consumption (L/h)	2.1
Running time (h)	6.6
Acoustic pressure	68 dB(A) - 7 m
Length (mm)	625
Width (mm)	448

Height (mm)	560
Dry weight (Kg)	50.5
Silenced	Yes
Voltage regulator	Inverter