

## PRAMAC GSW95P COFANATO CON QUADRO COMANDO AUTOMATICO

Reference: SU840TPAV02



### Technical Sheet

|                                    |  |
|------------------------------------|--|
| Phase                              | Three phase  |
| Maximum power three phase (KW)     | 73.93  |
| Continuous power three phase (KW)  | 66.98  |
| Maximum power three phase (KVA)    | 92.41  |
| Continuous power three phase (KVA) | 83.72  |
| Fuel                               | Diesel   |
| Frequency (Hz)                     | 50   |
| Voltage (V)                        | 400  |
| Engine                             | PERKINS 1104D-E44TAG1, turbocharged                |
| Emissions Regulations              | Stage 3A   |
| Speed governor                     | Electronic   |
| Starting system                    | Electric   |
| Engine capacity (cm <sup>3</sup> ) | 4400   |
| Number cylinders                   | 4  |
| Cylinders' position                | In line  |
| Oil capacity (L)                   | 8  |
| Cooling                            | Water  |
| Alternator                         | Mecc Alte ECP34-1S/4, brushless                    |
| Poles                              | 4  |
| Fuel tank capacity (L)             | 209  |
| Consumption (L/h)                  | 16.9 at 75% of the load / 20.4 at 100% of the load |

|                     |  |
|---------------------|--|
| Running time (h)    | 12.4 at 75% of the load / 10.2 at 100% of the load |
| Acoustic power      | 96 dB(A)   |
| Acoustic pressure   | 67 dB(A) at 7 m                                    |
| Length (mm)         | 2400   |
| Width (mm)          | 1000   |
| Height (mm)         | 1685   |
| Dry weight (Kg)     | 1490   |
| Silenced            | Yes  |
| Super silenced      | Yes  |
| ATS Switch device   | Optional ATS                                       |
| Voltage regulator   | AVR  |
| Engine manufacturer | Perkins  |