



## **POWERMATE WX3200 SINGLE PHASE GENERATOR 3.69 KVA AVR**

Reference: PR242SXIZ00

### **POWERMATE WX3200 SINGLE PHASE GENERATOR 3.69 KVA AVR**

POWERMATE WX3200 is a single-phase generator equipped with a 4-stroke gasoline engine, capable of delivering a maximum power of 3,69 KVA complete with AVR voltage regulator.

The POWERMATE WX3200 is equipped with sturdy handles and wheels that allow easy portability; like the entire POWERMATE WX3200 range, it is a generator set that meets high quality standards and guarantees a high level of reliability.

The strong points of the POWERMATE WX3200 are: the high quality of the components, lightness, compactness, portability and ease of use and also the modern design. The single-phase 3KVA generator is equipped with a manual rope starter.

The POWERMATE WX3200 has been specially developed for camping, caravans, homes, and hobby applications, etc., so it reflects the special features and comfort that allow its reliability and convenience in the areas of application.

The POWERMATE WX3200 is also equipped with an hour meter, an oversized fuel tank for extended runtime and a rain cover for use in bad weather.

#### **Advantages of the AVR voltage regulator**

The automatic voltage regulator, or AVR, allows the single-phase generator 3KVA to deliver stable energy and then be able to connect equipment with delicate electronics such as computers, appliances, smartphones and tablets: the genset is therefore ideal for home use, camping, hobbies and leisure, but also for construction sites and craftsmen.

The AVR and the high quality alternator with copper windings will provide you with safe and stabilized energy.

#### **Technical specifications of the POWERMATE WX 3200**

Phase Type: SinglePhase  
SinglePhase Continuous Power: 3.06 KVA / 2.45 KW  
SinglePhase Maximum Power: 3.69 KVA / 2.95 KW  
VAC voltage: 230 V  
Frequency (Hz): 50  
Voltage regulator: AVR  
Starting framework: Manual with self-winding  
Engine: OHV 4-stroke  
RPM: 3000  
Power supply: Gasoline  
Tank capacity: 17 l  
Consumption @ 75 % of load: 1.29 l/h

Autonomy @ 75 % of load: 13.1 h  
 Sound pressure: 65 dB(A) @ 7m  
 Length: 685 mm  
 Width: 505 mm  
 Height: 520 mm  
 Net weight: 49 Kg

Are you looking for a generator with different technical characteristics? [Here](#) you can find the area dedicated to POWERMATE generators or other specialized brands

Images and data are not binding and may be subject to revisions.

## Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	2.95
Continuous power single phase (KW)	2.45
Maximum power single phase (KVA)	3.69
Continuous power single phase (KVA)	3.06
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	2 x 230V
Engine	OHV 4 tempi
Emissions Regulations	Stationary Use
Engine rpm (rpm)	3000
Speed governor	Mechanical
Starting system	Pull starter
Cooling	Air
Fuel tank capacity (L)	17
Consumption (L/h)	1.3 at 75% of the load
Running time (h)	13.1 at 75% of the load / 10 at 100% of the load
Acoustic pressure	65 dB(A) at 7 m
Length (mm)	685
Width (mm)	505
Height (mm)	520
Dry weight (Kg)	49
Silenced	No
Super silenced	No
ATS Switch device	No ATS

---

Voltage regulator	AVR
Engine manufacturer	OHV

---