



POWERMATE WX 6200 SINGLE PHASE GENERATOR 7.25 KVA AVR RECOIL STARTER

Reference: PR532SXIZ00

POWERMATE WX 6200 SINGLE-PHASE GENERATOR 7.25 KVA AVR

POWERMATE WX 6200 is a single-phase generator equipped with a 4-stroke gasoline engine capable of delivering a maximum power of 7,25 KVA complete with AVR voltage regulator.

The POWERMATE WX 6200 is equipped with sturdy handles and wheels that allow easy portability; like the entire POWERMATE WX 6200 range, it is a generator set that meets a high quality standard and guarantees a high level of reliability.

The strengths of the POWERMATE WX 6200 are: the high quality of components, light weight, compactness, portability and ease of use and also modern design. The single-phase 7.25 KVA POWERMATE WX 6200 is equipped with a manual rope starter.

The POWERMATE WX 6200 has been specially developed for camping, caravans, homes, and hobby applications, etc., so it reflects special features and convenience that allow it to be reliable and comfortable in the application areas.

The advantages of the AVR voltage regulator

The automatic voltage regulator, or AVR, enables the single-phase 7.25 KVA generator to deliver stable power and thus be able to connect equipment with delicate electronics such as computers, household appliances, smartphones and tablets: the generator set is therefore ideal for use at home, camping, hobby and leisure, as well as for construction sites and craftsmen.

The AVR voltage regulator and the other quality standard of the alternator with copper windings will provide you with safe and stabilized power.

The AVR is the ideal generator for use at home, camping, hobby and leisure, as well as for construction sites and craftsmen.

Technical Features of the POWERMATE WX 6200

Phase Type: Single-Phase
Continuous Single-Phase Power: 6.63 KVA / 5.3 KW
Maximum Single-Phase Power: 7.25 KVA / 5.8 KW
VAC Voltage: 230 V
Frequency (Hz): 50
Voltage Regulator: AVR
Starting Frame: Manual with Self Wrap
Engine: OHV 4-Stroke
Emission Standard: Stage V
RPM: 3000
Power supply: Gasoline

Fuel tank capacity: 26 l
 Consumption @ 75 % load: 2.17 l/h
 Autonomy @ 75 % load: 12 h
 Sound pressure: 69 dB(A) @ 7m
 Length: 810 mm
 Width: 625 mm
 Height: 607 mm
 Net weight: 78 Kg

Looking for a generator with different technical characteristics? [Here](#) you can find the area dedicated to POWERMATE generators or other specialized brands

Pictures and data are not binding and may be subject to revisions.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	5.8
Continuous power single phase (KW)	5.3
Maximum power single phase (KVA)	7.25
Continuous power single phase (KVA)	6.63
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Engine	
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Speed governor	Mechanical
Starting system	Pull starter
Cooling	Air
Fuel tank capacity (L)	26
Consumption (L/h)	2.16
Running time (h)	12
Acoustic pressure	69 dB(A) at 7 m
Length (mm)	
Width (mm)	625
Height (mm)	606
Dry weight (Kg)	78
Inverter	No

AVR	Yes
Compound	No
Silenced	No
Super silenced	No
ATS Switch device	No ATS
Voltage regulator	AVR
