



VISA F 20 FOX GENERATOR SILENCED THREE-PHASE 22KVA AVR

Reference: F 20 FOX

VISA F 20 FOX 22KVA SILENT THREE-PHASE AVR GENERATOR

The VISA F 20 FOX three-phase generator is equipped with a diesel-powered FPT IVECO R24MAFS01.23 engine and is capable of delivering a maximum power of 22KVA, complete with an AVR voltage regulator.

The VISA F 20 FOX generator is compact and easy to use, featuring a canopy with sound-absorbing panels that significantly reduce noise emissions and make it **super-silenced**.

The generator is composed of a STAMFORD S0L2-G alternator with an AVR voltage regulator, allowing it to be used even with equipment sensitive to power surges.

The AVR is a device that allows you to **maintain a more constant output and reduce load dependence**. This card reduces power drops or spikes, making the various connected appliances safer to use, improving their performance and durability.

The generator features an electric start and low fuel consumption, consuming only 5.10 liters/hour at 75% load for up to 9 hours of operation. The generator ensures efficient and quiet operation thanks to the FPT IVECO R24MAFS01.23 engine, which delivers a maximum power of 22kVA. It is also equipped with automatic starting via an ATS panel, which allows it to start autonomously in the event of a blackout.

TECHNICAL CHARACTERISTICS OF THE VISA F 20 FOX

Phase type: Three-phase
Continuous power: 20 KVA / 16 KW
Maximum power: 22 KVA / 17.6 KW
Engine: FPT IVECO R24MAFS01.23
Power supply: Diesel
Engine speed: 1500 rpm
Alternator: STAMFORD S0L2-G
Starting: Electric / Automatic
Voltage regulator: AVR
Voltage: 400 V
Frequency: 50 Hz
Socket panel: Terminal block
Tank capacity: 50 l
Consumption at 75% load: 5.10 l/h
Runtime at 75% load: 9.80 h
Length (mm): 1660
Width (mm): 770
Height (mm): 1330
Dry weight (kg): 710

Are you looking for a product with different technical characteristics? [HERE](#) you can find the entire other specialized brands.

Images and technical data are not binding. Please always consult the manufacturer's technical data sheet. Manel Service assumes no responsibility for any modifications made by the manufacturer.

Technical Sheet

Phase	Three phase
Engine	FPT IVECO R24MAFS01.23
Maximum power three phase (KW)	17.6
Continuous power three phase (KW)	16
Maximum power three phase (KVA)	22
Continuous power three phase (KVA)	20
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Sockets configuration	Terminal box
Emissions Regulations	Stage 3
Engine rpm (rpm)	1500
Starting system	Electric / Automatic
Cooling	Water
Alternator	STAMFORD S0L2-G
Poles	4
Fuel tank capacity (L)	50
Consumption (L/h)	5.10
Running time (h)	9.8
Length (mm)	1660
Width (mm)	770
Height (mm)	1330
Dry weight (Kg)	710
Silenced	Yes
Super silenced	Yes
Product type	Generator
Voltage regulator	AVR
Engine manufacturer	FPT Iveco