



ITALTOWER SHIELD HYBRID PRO SKID-S LIGHT TOWER 6x100W LED STAGE V

Reference: SHIELD HYBRID PRO SKID-S

ITALTOWER SHIELD HYBRID PRO SKID-S 80,000lm Stage V Light Tower

The ITALTOWER SHIELD HYBRID PRO SKID-S is a light tower equipped with LED floodlights delivering a total of 80,000 lm, capable of illuminating an area of 4,400 square meters.

The ITALTOWER SHIELD HYBRID PRO SKID-S features a practical hydraulic lifting system that allows it to extend to a maximum height of 7 meters. Once fully extended, the light tower offers wind stability up to 110 km/h.

The ITALTOWER unit is equipped with 6 LED floodlights, each rated at 100W.

ITALTOWER SHIELD HYBRID PRO SKID-S Technical Specifications

Light type: 6x100W LED
Frequency: 50 Hz
Power: 3.5 kW
Engine: Yanmar 2TNV70
Fuel: Diesel
Emissions: Stage V
Alternator: Linz Alumen
Total lumens: 80,000 lm
Number of panels: 4
Height: 7 m
Lifting system: Hydraulic
Wind resistance: 110 km/h
Sound pressure: 61 dB @ 7 m
Dimensions: 245x118x118 cm
Weight: 1,100 kg

Are you looking for a product with different characteristics? [HERE](#) you can find the entire range of ITALTOWER lighting towers or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the supplier.

Technical Sheet

Phase	Single phase
Engine	Yanmar 2TNV70
Fuel	Diesel
Frequency (Hz)	50
Emissions Regulations	Stage 5
Engine rpm (rpm)	1500
Number cylinders	2
Cooling	Liquid
Alternator	Linz
Power (KW)	3.5
Maximum height (m)	7
Tank capacity (L)	240
Type of lamps	LED
Lamps	6 x 100 W
Illuminated area (m ²)	4400
Lifting System	Hydraulic lifting system
With generator / Without generator	With generator
Transportability	Stationary
Stability to wind (Km/h)	110
Acoustic pressure	61 dB(A) at 7 m
Dimension (cm)	245x118x118