



PRAMAC PX3250

Reference: PB252SH1003 /

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	2.6
Continuous power single phase (KW)	2.2
Maximum power single phase (KVA)	2.8
Continuous power single phase (KVA)	2.3
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	2 x 230V 16A IP54 SCHUKO
Engine	Honda GP160, naturally aspirated
Engine rpm (rpm)	3000
Speed governor	Mechanical
Ignition	Recoil
Starting system	Pull starter
Engine capacity (cm ³)	163
Oil capacity (L)	0.58
Cooling	Air
Alternator	Brushless
Poles	2
Fuel tank capacity (L)	3.1
Consumption (L/h)	0.88 at 75% of the load / 1.16 at 100% of the load

Running time (h)	3.52 at 75% of the load / 2.65 at 100% of the load
Acoustic power	95 dB(A)
Acoustic pressure	71 dB(A) at 7 m
Length (mm)	625
Width (mm)	455
Height (mm)	455
Dry weight (Kg)	38
Silenced	No
Super silenced	No
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	Capacitor
Engine manufacturer	Honda