



## PRAMAC P4500

Reference: PF322SY4008 /

### Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	3.7
Continuous power single phase (KW)	3.1
Maximum power single phase (KVA)	4.1
Continuous power single phase (KVA)	3.5
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x 230V 16A 2P+T CEE - 1 x 230V 32A 2P+T CEE - 1 x 230V 16A SCHUKO
Engine	Yanmar L70N Electric, naturally aspirated
Engine rpm (rpm)	3000
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm <sup>3</sup> )	320
Oil capacity (L)	1.1
Cooling	Air
Poles	2
Fuel tank capacity (L)	18
Consumption (L/h)	0.93 at 75% of the load / 1.24 at 100% of the load
Running time (h)	19.35 at 75% of the load / 14.52 at 100% of the load
Acoustic power	96 dB(A)

Acoustic pressure	68 dB(A) at 7 m
Length (mm)	800
Width (mm)	520
Height (mm)	690
Dry weight (Kg)	99
Silenced	Yes
Super silenced	No
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	Capacitor
Engine manufacturer	Yanmar